

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>OTTAWA</u>	<u>SW</u> 1/4 <u>SE</u> 1/4 <u>SE</u> 1/4	<u>6</u>	T <u>11</u> S	R <u>3</u> E/W

Distance and direction from nearest town or city street address of well if located within city?
520 E. LAUREL

2 WATER WELL OWNER: GREG PETRAKIS
 RR#, St. Address, Box # : 520 E. LAUREL Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : MINNEAPOLIS, KS. 67467 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>97.8</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>61</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>61</u> ft. below land surface measured on <u>mo/day/yr</u> <u>4-25-97</u>
	Pump test data: Well water was <u>66</u> ft. after <u>1</u> hours pumping <u>10</u> gpm
	Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter <u>9</u> in. to <u>98</u> ft., and in. to ft.

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
<u>2 PVC</u>	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 5 in. to 77 ft., Dia 160 in. to ft., Dia in. to SDR 26 ft.
 Casing height above land surface 14 in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot <u>.035</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 77 ft. to 97 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 55 ft. to 97.8 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 2 ft. to 25 ft., From 52 ft. to 55 ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? WEST How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	FILL DIRT			
2	13	CLAY RED SILTY			
13	22	SANDSTONE RED SOFT			
22	98	SANDSTONE TAN MED. HARD			
98		SHALE LIGHT GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-25-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 4-25-97 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY