

1 LOCATION OF WATER WELL: County: Ottawa Fraction SW 1/4 SE 1/4 SE 1/4 Section Number 13 Township Number T 11 S Range Number R 3 XEW

Distance and direction from nearest town or city street address of well if located within city? 4 miles North & 1/4 mile West of Bennington, KS 67422

2 WATER WELL OWNER: Bryan Wheeler RR#, St. Address, Box #: 1776 Ivy Road City, State, ZIP Code: Bennington, KS 67422 Board of Agriculture, Division of Water Resources Application Number: N/A

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants and an 'X' in the SE quadrant. A 1-mile scale bar is shown to the left.] 4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: WELL'S STATIC WATER LEVEL: 15 ft. below land surface measured on 10/9/98. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield 1.0-1.5 gpm: Well water was ... ft. after ... hours pumping ... gpm. Bore Hole Diameter: 9 in. to 6.1 ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well X Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Threaded. Blank casing diameter: 5 in. to 4.0 ft., Dia ... in. to ... ft., Dia ... in. to ... ft. Casing height above land surface: 12 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214. TYPE OF SCREEN OR PERFORATION MATERIAL: X PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot X Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 20 ft. to 60 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X Bentonite 4 Other. Grout Intervals: From 0 ft. to 2.0 ft., From ... ft. to ... ft., From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage X6 Other (specify below) 13 Insecticide storage Old well. Direction from well? Southwest How many feet? 200

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-2 Topsoil, 2-6 Tan Clay, 6-12 Tan Sandstone, 12-15 Gray Shale, 15-60 Light Tan Sandstone, 60-61 Gray Shale.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X(1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/9/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 10/30/98 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peters

OFFICE USE ONLY T R EW SEC 1/4 1/4 1/4