

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: OTTAWA	NW ¼ NW ¼ SW ¼	29	T 11 S	R 3W EW

Distance and direction from nearest town or city street address of well if located within city?
3/8 OF MILE NORTH OF INTERSECTION GRANITE RD. AND 130th OTTAWA COUNTY PERMIT # 00-208

2 WATER WELL OWNER: GIL THROWER
 RR#, St. Address, Box # : 6670 BROOK PARK DR.
 City, State, ZIP Code : COLORADO SPRINGS, CO. 80918
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>96'8"</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>80</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr <u>8-19-00</u>
	Pump test data: Well water was <u>82</u> ft. after <u>4</u> hours pumping <u>12</u> gpm
	Est. Yield <u>25+</u> gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: <u>9</u> in. to <u>105</u> ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes. No. <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No	

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. <u>X</u> Clamped.
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded.
		7 Fiberglass		Threaded.

Blank casing diameter 9 in. to 86'6" ft., Dia. 160 in. to ft., Dia. in. to ft.
 Casing height above land surface 24 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	<u>7 PVC</u>	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<u>3 Mill slot .025</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 86'6" ft. to 96'6" ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 26 ft. to 75 ft., From 78 ft. to 96'6" ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 26 ft., From 75 ft. to 78 ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>OPEN PASTURE NONE APPARENT</u>

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOP SOIL			
1	6	SANDSTONE TAN			
6	10	CLAY LIGHT GRAY			
10	16	CREEK GRAVEL BROWN			
16	30	IRONSTONE BROWN			
30	32	SANDSTONE TAN			
32	36	SANDSTONE RED			
36	42	SANDSTONE GOLDEN			
42	60	SANDSTONE RED			
60	68	SANDSTONE GOLDEN			
68	78	SANDSTONE RED			
78	94	SANDSTONE TAN			
94	96.8	OPENCIVITY			
96.8	105	SAND FINE TAN, AND TREE WOOD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-19-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 388 This Water Well Record was completed on (mo/day/yr) 8-22-00 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]