w	ATER WELL RECO	RD Form WWC-5	KSA 82a-	1212 ID N	0	
1 LOCATION OF WATER WELL:	Fraction			ction Number	Township Numb	er Range Number
County: OTTAWA	NE 1/4	NE ¼ NE ½	4	21	T 11	s R 3W E/W
Distance and direction from nearest to	own or city street add	dress of well if located	within city?			
2 WATER WELL OWNER: BILI						· · ·
	O IVY RD.				Board of Agricu	Iture, Division of Water Resources
,	NEAPOLIS,K	5. 67467			Application Nur	
3 LOCATE WELL'S LOCATION WITH	4 DEPTH OF CO	MPLETED WELL	4.5	ft. ELEVA	TION:	
AN "X" IN SECTION BOX:	Depth(s) Groundy	vater Encountered	ı30	ft	. 2	ft. 3 ft.
N	WELL'S STATIC	NATER LEVEL2	8ft. be	ow land surfac	e measured on mo/day	//yr8-11-05-
Est Yield 4.0 gpm: Well water was ft after hours pumping						
- NW NE - WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
W 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) W 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well						
W	2 Irrigation	4 Industrial 7	omestic (ia)	wn & garden)	10 Monitoring weil	
SW SF	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			D 0	/ N- 37 - 14	
was a chemical bacteriological sample submitted to Department: 1es190						
1 1	Timeod			* •	ator tron Blomnootog.	Yes X No
5 TYPE OF BLANK CASING USED		Mrought iron	8 Concr	ata tila	CACINIC IOINTS	S: GluedX Clamped
1 Steel 3 RMP (S		Wrought iron Asbestos-Cement		ete tile (specify below		Welded Viamped
<u>2 PVC</u> 4 ABS	7	' Fiberglass				Threaded
Blank casing diameter5						
Casing height above land surface		in., weight	1.50		lbs./ft. Wall thickness	or guage No. SDR 26
TYPE OF SCREEN OR PERFORATION		- E9	7 PV		10 Asbesto	
1 Steel 3 Stainles 2 Brass 4 Galvan		Fiberglass Concrete tile	8 HI 9 AE	MP (SR) BS		Specify)sed (open hole)
SCREEN OR PERFORATION OPEN			ed wrapped	-	8 Saw cut	11 None (open hole)
	Mill slot • 025		wrapped		9 Drilled holes	
	Key punched	7 Torch				ft.
SCREEN-PERFORATED INTERVALS	3: From	3.5 ft. to	45	ft., From		ft. toft.
ODAVEL BACK NITEDVAL	From	ft. to		ft., From		ft. to ft. ft. to ft.
GRAVEL PACK INTERVALS	5: From	⊋.Vtt. to ft to	4 .7	tt., From ft From		ft. to ft.
	at cement	2 Cement grout				
Grout Intervals: From0.		ft., From	ft. 1			
What is the nearest source of possible		- D'		10 Livest	•	14 Abandoned water well
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool		7 Pit privy			=	15 Oil well/Gas well 16 Other (specify below)
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		8 Sewage lagoon 9 Feedyard		12 Fertilizer storage13 Insecticide storage		
Direction from well? NORTHEAS		o i ecuyaru		How mar	× 4.0	
FROM TO	LITHOLOGIC L	.OG	FROM	ТО	·	ING INTERVALS
0 12 SANDY	LOOM TAN					-
	TAN SILTY					
l !	FINE TAN					
43 45 CLAY	3ROWN					
					············	
7 CONTRACTOR'S OR LANDOWN	ER'S CERTIFICATION	ON: This water well we	e (1) constr	ucted (2) reco	netructed or (3) plugg	and under my jurisdiction and was
completed on (mo/day/year)						
Water Well Contractor's Licence No						
under the business name of PEST					signature)	Delen 10
INSTRUCTIONS: Use typewriter or ball point p	oen. <i>PLEASE PRESS FIRM</i>	ALY and PRINT clearly. Please				
and Environment, Bureau of Water, Geology S records. Fee of \$5.00 for each constructed we		St., Suite 420, Topeka, Kansas	66612-1367. Te	ephone 785-296-5	522. Send one to WATER WE	LL OWNEH and retain one for your