

1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 10 Township Number T 11 S Range Number R 32 ~~36W~~

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Eric Kohn / One Stop-Steve Moore/Agro-Petro, Inc.  
 RR#, St. Address, Box #: Hwy 40 & Smokey Hill Rd Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Oakley, KS 67748 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants and an 'X' in the NE quadrant. A 1-mile scale bar is on the left.]

4 DEPTH OF COMPLETED WELL: 135 ft. ELEVATION: RIM 3054.68 TDC 3054.29

Depth(s) Groundwater Encountered 1. 120 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ~~2977.0~~ ft. below land surface measured on mo/day/yr 10-2-95

Pump test data: Well water was 119.5 ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8.5 in. to 135 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only  Monitoring well MW 13

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 PVC 4 ABS 7 Fiberglass Welded Threaded 4TPEI

Blank casing diameter 3.998 in. to 4.500 in. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface in. weight 2.07 lbs./ft. Wall thickness or gauge No. 237

TYPE OF SCREEN OR PERFORATION MATERIAL:  PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot  Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 105 7 Torch cut 135 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 2920.07 ft. to 2950.07 ft. From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 2920.07 ft. to 2954.07 ft. From 101 ft. to 135 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:  Neat cement 2 Cement grout  Bentonite 4 Other

Grout Intervals: From 2954.07 ft. to 3054.68 ft. From 101 ft. to ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy  Fuel storage 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	35	Silt			
35	40	Clay			
40	45	Silt			
45	70	Sand			
70	80	Silt			
80	90	Sand			
90	100	Clay			
100	110	Sand			
110	120	Clay			
120	135	Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on (mo/day/yr) 10-9-95 under the business name of Coranco, Inc. by (signature) [Signature]

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4