


1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 County: Logan SW 1/4 SW 1/4 SE 1/4 5 T 11 S R 32

Distance and direction from nearest town or city street address of well if located within city?
 2 Miles West of Oakley

2 WATER WELL OWNER: Clarence Heyen Wanker Oil Co.
 RR#, St. Address, Box #: 311 S. Center Rt. 2 Box 14
 City, State, ZIP Code: Oakley, Ks. 67748 Wakeeney, Ks. 67672
 Board of Agriculture, Division of Water Resources
 Application Number: 950410

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 217 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 159 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 159 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 in. to 217 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 4.5 in. to 177 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thickness or gauge No. 248
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 177 ft. to 217 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 217 ft., From ft. to ft.

6 GROUT MATERIAL: 0 Neat cement 20 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface	185	198	Med. Sand
2	20	Loess	198	214	Sandy Clay w/Fine Sand
20	30	Clay	214	216	Med. Sand
30	34	Med. Sand	216	217	Shale
34	42	Clay & Caliche			
42	61	Cemented Sand w/Sandstone & Sand w/Clay Strks.			
61	75	Med. Sand & Gravel w/Rocks			
75	78	Caliche w/Clay & Some Sand			
78	102	Clay & Caliche Strks.			
102	135	Med. Sand & Gravel w/Clay			
135	150	Soft Sticky Clay w/Some Sand			
150	159.5	Sandy Clay w/Some Sand			
159.5	164	Med. Sand			
164	185	Sandy Clay w/Some Sand Strks			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-19-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 12-20-95 under the business name of Woofter Pump & Well, Inc. by (signature)