			WATER	1 WELL RECORD	Form vv	VC-5 KSA 828	1-1212			
1 LOCATION OF WATER WELL:			Fraction	OT:	C173	Section Number	1 44	p Number	Range N	
County: Logan Distance and direction from nearest town of			SE 1/4		SE 1/4	3	T 11	S	R 32	E(W)
			-		ed within d	ity?				
U.S	. Hwy 8	3 & U.S. Hwy	40 Oakl	ey, KS		·				
2 WATE	R WELL OV	VNER: Eric Ko	hn							
RR#, St.	Address, Bo	× # : Hwy 40	& Smokey	Hill Road			Board	of Agriculture, [Division of Wate	er Resource
City, State	, ZIP Code	: Oakley,	KS 6774	8			Applica	ation Number:		
3 LOCAT	E WELL'S L	OCATION WITH[4]		OMPLETED WELL	.135	ft. ELEVA	TION:	3055.34 T.	Ω•C•	, , <i>.</i>
_ AN "X"	IN SECTIO	N BOX:	epth(s) Groundy	water Encountered	1	ft. :	2	ft. 3		
τ Γ			. , ,	WATER LEVEL . N						
1	ı			test data: Well wat						
-	NW	NE	•	gpm: Well wat				•	, ,	O.
!	ļ.			ter6in. to						
¥ w -	¦			O BE USED AS:		•	8 Air conditio		Injection well	
-	i					water supply		•	•	halau.\
-	SW	SE	1 Domestic	3 Feedlot		d water supply	<u></u>		Other (Specify	
1	!	l ¦x l w	2 Irrigation	4 Industrial		and garden only				
<u> </u>				acteriological sample	submiπea					
-		· · · · · · · · · · · · · · · · · · ·	itted				ter Well Disinf		No 2	
		CASING USED:		5 Wrought iron		oncrete tile		JOINTS: Glued	•	
1 St		3 RMP (SR)		6 Asbestos-Cement	9 0	ther (specify below	w)	Welde	ed	
(2)P\		4 ABS		7 Fiberglass					ded	
Blank cas	ing diameter	in	. to	ft., Dia		n. to	ft., Dia	i	n. to	ft
Casing he	ight above I	and surface		in., weight	•	•	ft. Wall thickne	ess or gauge No	D	
TYPE OF	SCREEN O	R PERFORATION I	MATERIAL:		•) •vc	10	Asbestos-ceme	nt	
1 St	eel	3 Stainless s	teel	5 Fiberglass	Ē	RMP (SR)	11	Other (specify)		
2 Br	ass	4 Galvanized	steel	6 Concrete tile	9	ABS	12	None used (op-	en hole)	
SCREEN	OR PERFO	RATION OPENINGS	S ARE:	5 Gau	zed wrappe	eđ	8 Saw cut		11 None (ope	n hole)
1 Cc	ontinuous slo	ot (3)Mill:	slot	6 Wire	wrapped		9 Drilled ho	les		
2 Lo	uvered shut	ter 4 Key	punched	7 Torc	h cut		10 Other (sp	ecify)		
SCREEN-	PERFORAT	ED INTERVALS:		0 ft. to.	1.35	ft., Fro	m	ft. to) <i></i>	
				ft. to .						
(GRAVEL PA	CK INTERVALS:		ft. to .						
			From	ft. to		ft., Fro)	
6 GROU	Γ MATERIAL	_: 1 Neat cer	ment C	2 cement grout	(3)					
Grout Inte	rvals Fro	m 0 ft	to 123	ft., From		ft to	ft From	n .	ft to	
What is th		ource of possible co		,			tock pens		pandoned wate	
	eptic tank	4 Lateral		7 Pit privy		11 Fuel	•		l well/Gas well	
2 Sewer lines 5 Cess poo				8 Sewage lago					ther (specify below)	
3 Watertight sewer lines 6 Seepage				9 Feedyard			ticide storage	-		
	•	ver imes o Seepag	e pit	9 Feedyald			_			
FROM	rom well?	I	LITHOLOGIC L	OG	FRO	How ma	ny leetr	PLUGGING IN	NTERVALS	
0	53	SILTY CLAY	<u> Emilio Eddio E</u>			··· ···				
53	55	SAND GRAVEI	•							
	1		<u> </u>				ASP-5			***************************************
55	135	SILTY CLAY					ASF-J			
		-								
	 									
	<u> </u>	ļ								
7 CONT	PACTOR'S	OR LANDOWNED'S	CERTIFICATIO	ON: This water well v	vae (1) ac-	netruoted (0) re-	netrusted or f	3) pluggod usd	er my juriodicti	on and we
completed	on (mo/day	year)	590	This Water V		. and this reco	ora is true to the	e pest of my kno	wieage and be	⊪er, Kansa:) ⁄u
			٠ ٠. ٠	Inis Water V	well Hecor			16,1-X	1/4/	2//-
	business na					by (signa			Me	XX
				RMLY and PRINT clearly. P0001. Telephone: 913-296-					copies to Kansas D	epartment