


1 LOCATION OF WATER WELL: Fraction SW NE 1/4 NE 1/4 SE 1/4 Section Number 3 Township Number T 11 S R 32 E/W

Distance and direction from nearest town or city street address of well if located within city? 324 East Front Street Oakley KS

2 WATER WELL OWNER: Great Western Tire/Coastal Mart El Paso Corp.
 RR#, St. Address, Box #: 319 East Front Street 2 N. Nevada
 City, State, ZIP Code: Oakley KS 67748 226 Colorado Sp. CO 80903
 Board of Agriculture, Division of Water Resources
 Application Number: 2917.29

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL: 136 ft. ELEVATION: 2917.29 ft.

Depth(s) Groundwater Encountered: 1 ft. to 106 ft. to 136 ft. to 136 ft.

WELL'S STATIC WATER LEVEL: 121.90 ft. below land surface measured on mo/day/yr 7-19-04

Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm

Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm

Bore Hole Diameter: 8 in. to _____ ft., and _____ in. to _____ ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-21

Was a chemical/bacteriological sample submitted to Department? Yes. _____ No. X; If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes _____ No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. _____ Clamped. _____
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded _____
 7 Fiberglass Threaded. X

Blank casing diameter: 8 in. to 0 ft., Dia 8 in. to 106 ft., Dia _____ in. to _____ ft.

Casing height above land surface: 0.26 in., weight _____ lbs./ft. Wall thickness or gauge No. _____

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) _____
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 0.020" 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 7 Torch cut 9 Drilled holes

SCREEN-PERFORATED INTERVALS: From 106 ft. to 136 ft., From _____ ft. to _____ ft.
 From _____ ft. to _____ ft., From _____ ft. to _____ ft.

GRAVEL PACK INTERVALS: From 102 ft. to 136 ft., From _____ ft. to _____ ft.
 From _____ ft. to _____ ft., From _____ ft. to _____ ft.

6 GROUT MATERIAL: 1 Heat cement 2 Cement grout 3 Bentonite 4 Other Sand 102 ft to 136 ft.

Grout Intervals: From 0 ft. to 2.0 ft., From 2.0 ft. to 100.0 ft., From 100.0 ft. to 102.0 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? _____ How many feet? _____

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5'	Concrete	74.0	86.0	Sandy clay, light brown, fine to med sand w/ white caliche, no odor
0.5'	2.0	Silty clay, brown backfill, no odor			
2.0	18.0	Sandy silt, yellowish brown, very fine to fines w/ no odor	86.0	95.0	Sand, med to very coarse, poorly sorted, subrounded to angular, light brown clay and caliche lenses, no odor
18.0	25.0	Clay, brown, fine sand, no odor			
25.0	38.0	Sandy clay, lt brown, fine to med sand w/ caliche no odor to slight odor @ 35'	95.0	101.0	Sandy clay, brown, fine to med sand, some iron staining, no odor
38.0	46.0	Sand, med to very coarse grains, poorly sorted, subrounded to angular, slight odor	101.0	106.0	Sand, fine to coarse grain w/ brown sandy clay, no odor
46.0	57.0	Sand, fine to med, random gravel, well sorted, slight odor	106.0	111.0	Sandy clay, brown, fine to med. sand, some white caliche, no odor
57.0	65.0	Sand, med to coarse, few very coarse grains, fairly well sorted, no odor	111.0	133.0	Sand, med to very coarse, poorly sorted, subrounded to angular, no odor
65.0	67.0	Caliche, white, hard, no odor			
67.0	74.0	Sand, fine to very coarse, poorly sorted, subrounded to angular, caliche stringers, no odor	133.0	136.0	Caliche and clay

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-19-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. #554 This Water Well Record was completed on (mo/day/yr) 8/18/04 under the business name of Wootte Pumpwell by (signature) J Wootte