

Corrected




WATER WELL RECORD Form WWC-5 1325288 Division of Water Resources App. No. Well ID MW-11R

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Logan Fraction NE 1/4 NE 1/4 NW 1/4 NE 1/4 Section Number 3 Township Number T 11 S Range Number R 32 E W

2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Country Club Motel--709 Center Ave



3 LOCATE WELL WITH 'X' IN SECTION BOX: N W E S

4 DEPTH OF COMPLETED WELL: 145 ft. Depth(s) Groundwater Encountered: 1) 129 ft. 2) ft. 3) ft. or 4) Dry Well WELL'S STATIC WATER LEVEL: 129.11 ft. below land surface, measured on (mo-day-yr) 12/28/2016

5 Latitude: 39.1330 (decimal degrees) Longitude: 100.85409 (decimal degrees) Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model) (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper: Elevation: 3054 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID MW-11R 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 4 in. to 115 ft. Diameter 2.071 in. to lbs./ft. Wall thickness or gauge No. 237

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 115 ft. to 145 ft. GRAVEL PACK INTERVALS: From 112 ft. to 146 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other GROUT INTERVALS: From 0 ft. to 112 ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? Distance from well? ft.

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows include surface, loess, fine & med sand & gravel w/clay lenses, clay & sandy clay w/caliche lenses, fine & med sand & gravel w/clay strks & c, clay & caliche w/sand strks, fine to some med sand w/clay & caliche st, fine & med sand & gravel w/clay lenses. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 12/19/2016 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 881. This Water Well Record was completed on (mo-day-year) 12/29/2016 under the business name of Woolter Pump and Well, Inc.