


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 24 Township Number T 11 S Range Number R 35 E/W
 County: Logan
 Distance and direction from nearest town or city street address of well if located within city?

211 E. Main, Page City

2 WATER WELL OWNER: John Haug Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: P.O. Box 91 Application Number:
 City, State, ZIP Code: Winona, Kansas 67764

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 137 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 110 ft. 2. 110 ft. 3. 110 ft.
 WELL'S STATIC WATER LEVEL 110 ft. below land surface measured on mo/day/yr 10-9-87
 Pump test data: Well water was not tested ft. after not tested hours pumping not tested gpm
 Est. Yield not tested gpm: Well water was not tested ft. after not tested hours pumping not tested gpm
 Bore Hole Diameter: 8 in. to 1.37 ft., and not tested in. to not tested ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes not tested No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 1.17 ft., Dia. 1.8 in. to 1.8 ft., Dia. 1.8 in. to 1.8 ft.
 Casing height above land surface 18 in., weight 1.8 lbs./ft. Wall thickness or gauge No. 1/4"
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 117 ft. to 137 ft., From 117 ft. to 137 ft.
 GRAVEL PACK INTERVALS: From 18 ft. to 137 ft., From 18 ft. to 137 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 4 ft. to 18 ft., From 4 ft. to 18 ft., From 4 ft. to 18 ft., From 4 ft. to 18 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? north How many feet? 180

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	32	top soil			
32	64	sandy clay			
64	110	sand and clay sbbips			
110	114	sand			
114	134	sandy clay and sand strips			
134	137	oker and shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-9-87 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 139 This Water Well Record was completed on (mo/day/yr) 6-27-88
 under the business name of Bartell Drilling by (signature) James Bartell

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4