			10/ 0 T	ER WELL BECOE	2D Farm \	MAIC 5	VCV 820	1212				
WATER WELL RECORD 11 LOCATION OF WATER WELL: Fraction						Section Number			Township Number Range Numb			
County:		TICIN VVICE.	NW 1/	SE 1/4	SE ¼	1	1	T 1	•	R 4	BM	
		on from nearest t	address of well if			1	<u> </u>	1 0	1 11 -			
1			Pipe St, Minne		located with	iii City :						
I			•	=								
			Dept. of Health &	Env.								
RR#, St. A		т .	Kansas 66620						_	ision of Water	Resources	
City, State	·	· · · · · · · · · · · · · · · · · · ·	. Kansas 00020					Application	Number:			
3 LOCATI	E WELL'S	LOCATION ECTION BOX:	4 DEPTH OF C	OMPLETED WEL	.L 51		ft. ELEV	ATION:				
VIIIA		N BOX:	Depth(s) Groun	dwater Encounter	ed 1		. ft .	2	ft.	3	ft	
WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day.												
T		NE E	Pump test data: Well water was									
	NW											
0												
w L			1	TO BE USED AS				8 Air condition		Injection well		
-	sw	s _x	1 Domestic		6 Oil fiek	,		9 Dewatering	-	Other (Specifi	. halana	
			İ							` ' '	, pelow)	
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? YesNo									
♦]	vvas a chemica								' /	
		S								No		
5 TYPE C	OF BLANK	CASING USED:		5 Wrought iron	_	Concrete				ed Clan	'	
1 St		3 RMP(S	R)	6 Asbestos-Cer		Other (spe				ded	1	
(2)P\		4 ABS		7 Fiberglass						aded	i	
Blank casir	ng diamete	r .2	in. to3	31 ft., Dia .		. in. to .		ft., Dia		in. to	ft.	
Casing hei	ght above	and surface	0	. in., weight	Sch 4	10	lbs./f	t. Wall thickn	ess or gauge	No		
_	-	R PERFORATIO		•		PVC			Asbestos-cen			
1 Ste	eel	3 Stainles	s steel	5 Fiberglass		RMP (S	SR)	11	Other (specify	/)		
2 Br	4 Galvaniz		9 ABS 12 None used (open hole)									
		RATION OPENIN		6 Concrete tile	Sauzed wrap			8 Saw cut	110110 0000 (0	11 None (op	en hole)	
	_											
1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut											-	
		ED INTERVALS		3.1 ft.		:1			• •			
SCREEN	- ERI-ORA	ED INTERVALS		ft.								
6	DAVEL DA	CK INTERVALS		. 25.4 ft.								
		ICK HAIENVALS		ft.								
6 GROUT				2 Cement grout		Bentonite						
Grout Inter	vals: Fro	m	. ft. to 19	ft., From .	19 —	ft. to .	25.4	ft,Fron	n	ft. to	ft.	
What is the nearest source of possible contamination:						10 Livestock pens				14 Abandoned water well		
1 Septic tank 4 Lateral lines 7 Pit privy						11 Fuel storage				15 Oil well/Gas well		
2 Sewe	2 Sewer lines 5 Cess pool 8 Sewage lagoon						12 Fertilizer storage (16 Other (specify below)					
3 Wate	er lines 6 See	ard		13 Insec	ticide storage	ب	Jnknown	pelow)				
Direction f	rom well?		•			How man	y feet?					
FROM	10	1	LITHOLOGIC	TOG	FRO	OM	10		PLUGGING	NTERVALS		
0	1	Fill gravel,										
1	10		ellowish Brow	/n						- 1490		
	12		ark Reddish I									
10												
12	32	Sandstone, Grayish Orange						·				
32	52	Sandy Silt, B	rownish Black	<u> </u>								
				· · · · · · · · · · · · · · · · · · ·								
								IW8 , Flushme	ount			
								roject Name:		olis PWS #12		
								eoCore # 764				
3		<u> </u>			" 0			(2) reconstructed, or (3) plugged under my jurisdiction				

×