CORRECTED	WATER WELL RE	CORD Form W	WC-5 KSA 82a-				
1 LOCATION OF WATER WELL:	Fraction		Section Number	Township Nur	nber	Range Num	ber
County: Ottawa	½ NW ½		1	T 11	S F	₹ 4	₽₩)
Distance and direction from nearest town	-	ell if located within	city?				
524 W. 2nd Street, Minneapolis, l	Kansas						
2 WATER WELL OWNER: Archer Dan	iels Midland						
RR#, St. Address, Box # : P. O. Box 1				Board of Agricul	ture. Division	of Water Res	Ources
City, State, ZIP Code Decatur, III	inois 62525			Application Num			
	DEPTH OF COMPLETED V	VFII 62	ft FI FVA				
→ WITH AN "X" IN SECTION BOX: 니	oth(s) Groundwater Encou						
	ELL'S STATIC WATER LE						
<b>†</b>			NA ft. afte				
NW NE							
	Yield NA gpm: \						
= W	re Hole Diameter 12.75						f
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ELL WATER TO BE USED			Air conditioning	'	tion well	
sw X <sub>SE</sub>	1 Domestic 3 Feedl			Dewatering		er (Specify be	
	2 Irrigation 4 Indus	trial 7 Lawn ar	d garden only 10	) Monitoring well	Reu	very Wel	1
<b>V</b> 1 1 1 1	as a chemical/bacteriologic	cal sample submit					,
3	omitted			er Well Disinfected		No √	
TYPE OF BLANK CASING USED:	5 Wrought		oncrete tile			•	
1 Steel 3 RMP (SR)	6 Asbestos-	Cement 9 O	ther (specify below	")			
2 PVC 4 ABS	7 Fiberglass						
Blank casing diameter 8 in							
Casing height above land surface 1.4	weight.	<u></u>	lbs./ft.	Wall thickness o	r gauge No	160.Lb	• · · · · ·
TYPE OF SCREEN OR PERFORATION M	ATERIAL	(7)PVC		10 Asbestos-cement			
1 Steel 3 Stainless ste	el 5 Fiberglass	5 Fiberglass 8 RMP (SR)		11 Other	(specify)		
2 Brass 4 Galvanized s	teel 6 Concrete	tile 9	ABS	12 None	used (open h	ole)	
SCREEN OR PERFORATION OPENINGS	ARE:	5 Gauzed wrappe	ed i	8 Saw cut	11	None (open l	nole)
1 Continuous slot 3 Mill sk	ot	6 Wire wrapped	9	9 Drilled holes			,
2 Louvered shutter 4 Key p	unched	7 Torch cut	1	Other (specify)			
SCREEN-PERFORATED INTERVALS: F	rom 42	ft. to 62					
F	rom	ft. to	ft., Fron	n	ft. to		f
GRAVEL PACK INTERVALS: F	From 37	ft. to 64	ft., Fron	n	ft. to		f
F	rom	ft. to	ft., Fron	n <b></b>	ft. to		f
GROUT MATERIAL: 1 Neat ceme	ent 2 Cement gro	out 3 B	entonite 4 C	Other			
Grout Intervals: From							
What is the nearest source of possible cor			10 Livesto			loned water w	
1 Septic tank 4 Lateral lin		orivo	11 Fuel st	•	15 Oil wel		GII
2 Sewer lines 5 Cess poo		vage lagoon	(12) Fertiliz	•		(specify below	w
2 Oction integ 0 Oceas poor	0 361	age lagoon	LIZI GIUIZ	c, storage	io Calei	(Shecity nem)	**)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? 40 Direction from well? LITHOLOGIC LOG PLUGGING INTERVALS FROM FROM 0 7 Sand, Brown Sandstone, Brown 7 52 52 Sandstone, Red Brown 55 55 64 Sandstone, Brown RECEIVED JUN 0 8 2006 **BUREAU OF WATER** 

Project Name: Huff Huff ADM Minneapolis GeoCore # 992 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 11 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and this record is true to the best of my knowledge and belief. 

GeoCore Services, Inc.

under the business name of

RW- , Above Grade

by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.