<u> </u>		WA	ATER WELL RE	CORD Form WW	C-5 KSA 82a	-1212 ID N	o	
1 LOCATIO	N OF WATE	R WELL:	Fraction NE	SE 1/2 NE	14 Se	ection Number	Township Number	Range Number
Distance and 215 E.		m nearest to	wn or city street	address of well if loca	ated within city?	,		
	VELL OWNE	R: OTTA	JA COUNTY	HEALTH CENTE	₹	·		· · · · · · · · · · · · · · · · · · ·
RR#, St. Addr City, State, Zi	ess, Box # P Code		AP OLIS, K	5.67467			Application Num	
3 LOCATE W	ELL'S LOC	ATION WITH	4 DEPTH OF	COMPLETED WELL	147	ft. ELEVA	TION:	•••••••••••••••••••••••••••••••••••••••
AN "X" IN S	ECTION BO	OX:	Depth(s) Grou	indwater Encountered IC WATER LEVEL	86 1ft. be	ft. low land surfac	. 2 e measured on mo/day/	ft. 37-27-04 ft.
		,	Pı	imp test data: Well v	water was	ft. e	after ho	ours pumping gpm
N	w	NE - x		יאא gpm: vveil ו R TO BE USED AS:	s Public water			ours pumping gpm 11 Injection well
	!	-	1 Domesti		6 Oil field water	er supply	9 Dewatering	12 Other (Specify below)
W	1	`	2 Irrigation	1 4 Industrial	7 Domestic (la	wn & garden)	10 Monitoring well	······································
8	w	SE	Was a shamis	ni/baatarialariaal aam	anto automittad ta	Denominant?	/aa Na ¥ . 16.	yes, mo/day/yrs sample was sub-
		1	mitted	arbacteriological Sali	ipie submitted to		ater Well Disinfected? Yo	
5 TYPE OF	BLANK CA	SING USED:		5 Wrought iron	8 Conc	rete tile	CASING JOINTS:	Glued .X Clamped
1 Steel		3 RMP (SI	R)	6 Asbestos-Cemer		(specify below)	Welded
2 PVC	diameter	4 ABS	in to	7 Fiberglass			# Dia	Threaded
Casing height	above land	surface	12	in., weight	160		lbs./ft. Wall thickness or	guage No. SDR 26
		PERFORATIO	N MATERIAL:		_7.P	VC	10 Asbestos	s-Cement
1 Steel 2 Brass		3 Stainles: 4 Galvania		5 Fiberglass 6 Concrete tile	8 R 9 A	MP (SR) BS		pecify)ed (open hole)
SCREEN OR			NGS ARE:		Guazed wrapped Vire wrapped		8 Saw cut 9 Drilled holes	11 None (open hole)
1 Continu 2 Louver	ed shutter		ey punched	7 1	forch cut		10 Other (specify)	tt.
SCREEN-PE	RFORATED	INTERVALS:		127 ft. to	147	ft., From		. ft. toft.
CD.	AVEL DACK	INTERVALS	From	50 ft. to	147	ft., From		. ft. to
Gn.	AVEL FACE	INTERVALS	From	ft. to	·	ft., From		. ft. toft.
6 GROUT	MATERIAL:	1 Nac	1.000001	2 Coment and the	3 Pa-		l Other	
Grout Interval	s: From	9	t cement	2 Cement grout	<u>3 Ber</u>	tonite 4	ft From	ft. toft.
			contamination:	,		10 Livest		14 Abandoned water well
1 Septic tank 4 Late			ral lines	7 Pit p	rivy	11 Fuels	torage	15 Oil well/Gas well
2 Sewer lines 5 Ces			•		• •	•		16 Other (specify below)
3 Watert Direction from		nes 6 Seep NORTH		9 Feed	dyard	13 Insect	icide storage v feet? 30	
FROM	TO	MORTH	LITHOLOGI	C LOG	FROM	TO	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	NG INTERVALS
0	2	FILL DI						:
2	4 7	CLAY TA	n soft					
17	47		D TO GRAY					
47	147	SANDSTO	NE TAN			 -		
						 		· .
				militarian kan kan kan kan kan kan kan kan kan k				
			· · · · · · · · · · · · · · · · · · ·				and the same of th	
7 CONTRAC	TOR'S OR	LANDOWNE	R'S CERTIFIC	ATION: This water we	ell was (1) const	ructed, (2) reco	nstructed, or (3) plugge	d under my jurisdiction and was
completed on ((mo/day/yea	r) r — & y	388		Inter Mail Dece	and this rec	cord is true to the best of	od under my jurisdiction and was
under the busi	ness name	of PESTIN	IGER PUMP	SERVICE	aler vien Hecord		signature)	allet
and Environme	ent, Bureau of V	ter or ball point pe later, Geology Se constructed well.	ection, 1000 SW Jack	FIRMLY and <u>PRINT</u> clearly. I son St., Suite 420, Topeka, I	Please fill in blanks, ur Kansas 66612-1367. T	nderline or circle the elephone 785-296-5	correct answers. Seguitop three 522. Send one to WATER WELL	e copies to Kagisas Department of Health LOWNER and retain one for your