CORRECTED RECORD

Second S
MATER WELL OWNER: **Jim Koster R#. St. Address, Box # : **387 N. 130th Rd.** IV, State; ZIP Code : **Bennington, Ks. 67422
WATER WELL OWNER: 387 N. 130th Rd. Baard of Agriculture, Division of Water Res Application Number: Secritory Secretary Secreta
R. S.L. Address, Box # 387 N. 130th Rd Application
No.
DEPTH OF COMPLETED WELL 59
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1
An X* IN SECTION BOX:
WELL'S STATIC WATER LEVEL. 4.2. ft. below land surface measured on mo/day/yr. Pump test data: Well water was ft. after hours pumping best yield. 25 .gpm: Well water was ft. after hours pumping the water was the water was ft. after hours pumping the wate
Est Yield 2.5. gpm: Well water was
WELLWATER TO BE USED AS: 5 Public water supply 9 Dewatering 1 Injection well 1 Domestic 3 Feedot 6 Oil field water supply 9 Dewatering 1 Officer (Specify below) Stock well 1. SWSE
TYPE OF BLANK CASING USED: 1 Steel 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 5 Voter (Specify below) 5 SUCK WELL Was a chemical/bacteriological sample submitted to Department? Yes
Was a chemical/bacteriological sample submitted to Department? Yes
Was a chemical/bacteriological sample submitted to Department? Yes
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 7 Fiberglass Threaded. Ank casing diameter 5. in. to 49. ft., Dia in., weight 2.37 Ibs:/ft. Wall thickness or guage No. 10. 21.47 YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify). 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify). CREEN-PERFORATED INTERVALS: From 49. ft. to 59. ft., From ft. to From ft. to From ft. to ft., From ft. To ft. From ft. To ft., From ft. To ft., From ft. To ft., From ft. To ft., From ft.,
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 7 Fiberglass 7 Fiberglass 7 Fiberglass 9 Other (specify below) 7 Fiberglass 7 Fiberglass 9 Other (specify below) 8 Welded 1 Threaded 1 Rank casing diameter 5 In. in. to 1 In. From 1 In. to 1 In. to 1 In. In. to 1 In.
Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded ABS 7 Fiberglass Threaded ABS 7 Fiberglass Threaded ABS Threaded Threaded ABS Threaded Threaded ABS Threaded Threaded Threaded ABS Threaded
Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded ABS 7 Fiberglass Threaded ABS 7 Fiberglass Threaded ABS Threaded Threaded ABS Threaded Threaded ABS Threaded Threaded Threaded ABS Threaded
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Indicated Threaded Threaded
lank casing diameter 5. in. to 49. ft., Dia in. to ft., Dia in. to ft., Dia in. to saing height above land surface 12. in., weight 2.37. lbs./ft. Wall thickness or guage No. YPE OF SCREEN OR PERFORATION MATERIAL: YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 9 ABS 12 None used (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) CREEN-PERFORATED INTERVALS: From 49. ft. to 59. ft., From ft. to ft., From ft. to ft. From ft. The
Asing height above land surface
Asing height above land surface
1 Steel 2 Brass 4 Galvanized Steel 5 Fiberglass 8 \overline{RMP}(SR) 11 Other (Specify) 12 None used (open hole) CREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 \overline{KMill slot} 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
2 Brass
CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) CREEN-PERFORATED INTERVALS: From 49 ft. to 59 ft., From ft. to ft., From ft., From ft. to ft., From ft.,
1 Continuous slot 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) CREEN-PERFORATED INTERVALS: From 49 ft. to 59 ft., From ft. to ft., From ft. to ft. From ft. to ft., From ft.
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) CREEN-PERFORATED INTERVALS: From 49 ft. to 59 ft., From ft. to ft., From ft. to ft. From ft. to ft., From ft., From ft. to ft., From ft., From ft. to ft., From ft
CREEN-PERFORATED INTERVALS: From
From
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 6 rout Intervals: From 0 ft. to 20 ft., From That is the nearest source of possible contamination: None within 1/4 mile 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? FROM TO PLUGGING INTERVALS O 2 Topsoil 2 Sandstone, tan
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 6 rout Intervals: From 0 ft. to 20 ft., From That is the nearest source of possible contamination: None within 1/4 mile 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? FROM TO PLUGGING INTERVALS O 2 Topsoil 2 Sandstone, tan
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other fit to fit, From fit to fit to fit, From fit to fit, From fit to fit, From fit to fit to fit to fit to fit, From fit to fi
rout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft.,
That is the nearest source of possible contamination: None within 1/4 mile 10 Livestock pens 14 Abandoned water we 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS O 2 Topsoil 7 O PLUGGING INTERVALS
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS O 2 Topsoil 2 5 Sandstone, tan
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS O 2 Topsoil 2 5 Sandstone, tan
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS O 2 Topsoil 2 5 Sandstone, tan
How many feet? How many feet? FROM TO PLUGGING INTERVALS PLUGGING INTERVALS PLUGGI
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS O 2 Topsoil 2 5 Sandstone, tan
o 2 Topsoil 2 5 Sandstone, tan
2 5 Sandstone, tan
5 25 Shale, red
7 22 VANALU 195
25 31 Sanstone, light gray
31 39 Shale, red
39 46 Sandstone, light gray
46 80 Shale, red
SEP 1 6 2004
SUNEAU OF WATER
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction a
empleted on (mo/day/year)
ater Well Contractor's Licence No
der the business name of Peterson Irrigation, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.