			ATER WELL RE	CORD	Form WWC-5	KSA 82a	-1212 ID N						
			Fraction	< 11	4//	Se	Section Number		Township Number		Range Number		
			SE 1/2		1/4 NW	1/4	0	T	//	<u> </u>	R 7	EM	
$\overline{}$			wn or city street				7- 4	. 1/.					
2 WATER W		ER. M. H	1,5 mi	195	Dorth	OP C	Knmark	/45	<u> </u>		 		
RR#, St. Addre		-	E. Ryc					Boo	rd of Agricu	iltura Dis	vision of Water I	Casaurasa	
City, State, ZIF			an Grove		67481				lication Nur		vision of Water I	resources	
		ATION WITH	4 DEPTH OF	COMPLET	ED WELL	41	ft. ELEVA						
AN "X" IN SE			Depth(s) Grou			,							
	N	1				ft. b∈	low land surfac	e measured	d on mo/da	y/yr			
1		1									mping mping		
N/	w	- NE	WELL WATER			Public water		8 Air cond			ection well	дріп	
¥			1 Domesti			Oil field wat		9 Dewate		(12) Oth	ner (Specify bel	ow)	
W		 E	2 Irrigation	n 4 in	dustrial 7	Domestic (la	iwn & garden)	10 Monitor	ing weii		ivestock		
		! CE		10-1-	l ! l l -		D				(-1		
51	1	- 35	was a chemic	al/bacterio	logical sample	submitted to	Department? '	res No ater Well Di		-	day/yrs sample/ N		
1	<u> </u>		, made					4(0) 170,721	0111100104				
5 TYPE OF I	S S	ASING USED:	<u> </u>	E Mrou	aht iron	8 Cond	roto tilo	CASI	NG JOINTS	e: Gluad	Clampe		
1 Steel	DLAINK CA	3 RMP (S		5 Wrou 6 Asbe	stos-Cement		rete the r (specify below		ING JOHN I		d		
6 PVC		A ARC	,	7 Fibor	alace		, ,	,		Thread	ded		
Blank casing c	diameter	<i>C</i>	in. to	21	ft., Dia	11 C H	in. to		ft., Dia		in. to	ft.	
Casing height	above lan	d surface	in. to	in., v	veight	160	·····	lbs./ft. Wall	thickness	or guage	No		
TYPE OF SCREEN OR PERFORATION MATERIAL:					glass	7 7 P	VC MP (SR)		10 Asbeste	os-Ceme	nt		
1 Steel 2 Brass		4 Galvani		6 Conc		9 A			12 None u				
SCREEN OR	PERFORA	TION OPENII	NGS ARE:		5 Gua	zed wrapped		8 Saw c	ut		11 None (open	hole)	
1 Continu			Aill slot		6 Wire	e wrapped		9 Drilleo				,	
2 Louvere	ed shutter	4 F	ey punched	· .	7 Toro								
SCREEN-PEF	RFORATE) INTERVALS	: From	<u>ا</u>	ft. to	41	ft., From			ft. to		ft.	
GB/	AVEL PACI	K INTERVALS	From	20	tt. to ft to	41	ft., From			ft. to ft. to		ft.	
Grir	W LL 1 /10/	THE CONTECT											
C ODOUT !	AATEOLAL	4 N		0.0-		6.0-	-1	4. Other-					
Grout Intervals	ATERIAL:	: Nea	at cement ft. to	2.0° #	ment grout	G Be					ft to		
			contamination:		., 1 10111			tock pens	111		andoned water		
1 Septic tank 4 Lateral lines								torage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool					8 Sewage lagoon			12 Fertilizer storage			16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit					9 Feedya	9 Feedyard 13 Insec			ge	14.	sture		
Direction from	well?						How mar	ny feet?					
FROM	ТО		LITHOLOGI	IC LOG		FROM	ТО		PLUGO	ING INT	ERVALS		
	8	Clay	- brown			-							
	20	day -	light	brown			-						
	2 8 35	Clay-	- gray										
	10	Gravel											
The same of the sa	50	Shale								-			
/0		- Marc	-										
						_	-						
7 00							1						
CONTRACT	TOR'S OR	LANDOWNE	R'S CERTIFICA	ATION: Th	is water well v	vas (1) const	ructed, (2) reco	onstructed,	or (3) pluge	jed unde	er my jurisdictio	n and was	
Water Well Cor	ntractor's I	ar)	19/05		This Wate	r Well Becon	and trils re d was complete	ed on (mo/d	av/vr)	1 - 2	4 - 0.5	er. Narisas	
under the busir					Tino Trato		by ((signature)	1	1/	Rel		

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.