		WATER	WELL RECORD	Form WWC-8	5 KSA 82a	1212	
LOCATION OF		Fraction		Sec	ction Number	Township Number	Range Number
County: Lincol		SW 1/4	SW 1/4 SW	1/4	20 17	T 12 S	R 10 E/W
istance and direc	tion from nearest town	or city street add	dress of well if located	within city?			
Approx	imately 1½ mi	les south a	and $3 3/4 \min 16$	es west	of Sylvan	Grove	
WATER WELL	OWNER: Me:	yer Land &	Cattle		•		
RR#, St. Address,	Box # : C/6	o Chris Mey x 149					ire, Division of Water Resource
City, State, ZIP Co	de : Sy.	KS 67481	Application Number:				
LOCATE WELL	S LOCATION WITH 4	DEPTH OF CO	MPLETED WELL	.53	ft. ELEVA	rion: unknown	
AN "X" IN SEC							ft. 3
							y/yr
							s pumping gpm
NW -	· ··· NE ···· F						s pumping gpm
		Rore Hole Diamete	ar 10 in to	. was	ft r	and	in. toft.
W management		VELL WATER TO		5 Public wate			11 Injection well
· i		1 Domestic				w	•
SW .	SE	2 Irrigation	4 Industrial	7 Lown and	ner suppry	Dewatening Monitoring well	12 Other (Specify below) . Stock
					-		
(X '	prediction of the contract of		icteriologicai sample s	ubmitted to D			yes, mo/day/yr sample was sub
TANE OF DIAS	S IT	nitted				er Well Disinfected? Yes	
			5 Wrought iron	8 Concre			Blued Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Cement		(specify below	•	Velded
2 <u>PVC</u>	4 ABS		7 Fiberglass			т	hreaded
llank casing diam	eter Эir	າ. to	ft., Dia	in. to		ft., Dia	in. to ft.
			n., weight \dots 2 .	36	Ibs./1	t. Wall thickness or gaug	je No •214
	OR PERFORATION			7 PV	<u>'C</u>	10 Asbestos-c	
1 Steel	3 Stainless s	steel	5 Fiberglass 8 R		IP (SR)		cify)
2 Brass 4 Galvanized steel			6 Concrete tile 9 AB		S	12 None used	(open hole)
CREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped			8 Saw cut	11 None (open hole)
1 Continuous	slot 3 Mill	slot	6 Wire v	6 Wire wrapped		9 Drilled holes	
2 Louvered s	hutter 4 Key	punched	7 Torch			10 Other (specify)	
CREEN-PERFOR	ATED INTERVALS:	From	38 ft. to	5.3	ft., Fron	n . <i>.</i>	ft. toft.
							ft. toft.
GRAVEL	PACK INTERVALS:	From	20 ft. to	5.3	ft., Fror	n	ft. toft.
		From			ft., Fror		ft. to ft.
GROUT MATER	RIAL: 1 Neat ce	ment 2					Holeplug
Grout Intervals:	From						ft. to 20 ft.
	t source of possible co						4 Abandoned water well
· ·			7 Pit privy			storage 1	
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage		6 Other (specify below)
3 Watertight sewer lines 6 Seepage pit			9 Feedyard		13 Insecticide storage		
Direction from well		-	O i oodyala		How mar		
FROM TO	WICHILL II	LITHOLOGIC L	OG	FROM	TO		IG INTERVALS
0 3	Topsoil, ha						
3.5 13.			gray shale			***************************************	
13.5 24	Dakota yel		s gray bliate				114 15 \$4.00 000 000 000 000 000 000 000 000 000
24 54	Dakota san		an looco			164 - 41 - 641 775 1676	W.F. W.F. W.F. W.F. W.F. W.F. W.F. W.F.
54	Dakota roci		an, 1008e			The second secon	
	Dakota 100	K	////				
					-		
			11 10 10 10 10 10 10 10 10 10 10 10 10 1				
····	A 170 (111 (11 (11 (11 (11 (11 (11 (11 (11 (V			***	
						The second secon	
						MARKAGA	
							ALCOHOL MANAGEMENT AND A TON TO THE STATE OF
CONTRACTOR	S OR LANDOWNER'S	S CERTIFICATIO	N: This water well wa	as (1) constru	cted. (2) reco	nstructed, or (3) plugged	under my jurisdiction and was
ompleted on (mo	day/year) 2-4:						y knowledge and belief. Kansas
						on (mo/day/yr) /2-1	
nder the business					•	· // /	11///
	Hame of Otalke	METT & FUI	alpment. Inc.		by (signat	ure) 🧀 🧀	4011 0
INSTRUCTIONS				ease fill in blanks	by (signat		hree copies to Kansas Department