9607			WAT	ER WELL RECORD	Form	WWC-5	KSA 82a	-1212		
	ON OF WAT	ER WELL:	Fraction	And			ion Number	Township Numb	oer	Range Number
County:	Linc	:oln	NE 1	/4 NE 1/4 N	1E	1/4	20	т 12	S	R 10 E(W)
			wn or city street	address of well if loc	ated with	nin city?				
Appro	oximatel	Ly 3/4 mile	e south an	d 3 west of S	Sylvan	Grove	2			
WATER	WELL OW	NER:	Meyer La	nd & Cattle						
-4	Address, Box		c/o Chri Box 149	s Meyer				Board of Agric	culture. I	Division of Water Resource
City, State,		. ,,	Sylvan Grove, KS 67481 Application Number:							arrison of tracer modeling
		CATION WITH				32	4. FT FT / A	TION: unknown		New York Control of the Control of t
AN "X"	IN SECTION	BOX:								
i f		l X	WELL'S STATI	C WATER LEVEL .	32 ' 11'	ft. be	elow land sur	face measured on me	o/day/yr	6-13-91 mping gpm
-	- NW	NE	Est. Yield . un	knowngpm: Well v	vater was	3	ft. a	fter h	ours pu	mping gpm
<u>.</u>	i		Bore Hole Diar	neter. 8. , 3 / 4in.	to	80.,		and	in	. to
× -	I		WELL WATER	TO BE USED AS:	5 Pu	ıblic wate	supply	8 Air conditioning	11	Injection well
7		1	1 Domesti	c 3 Feedlot				9 Dewatering	12	Other (Specify below)
****	- SW	== 5E e= ==	2 Irrigation	4 Industrial	7 La	wn and g	arden only	10 Monitoring well	,	Stock
		aggin and and and and and and and and and an	Was a chemica	l/bacteriological samp	ole submi	itted to De	partment? Y	esNoX	; If yes,	, mo/day/yr sample was sub
Y boom		agente sensiti territoria de menurolita d	mitted	,			-	ter Well Disinfected?		X No
TYPE C	F BLANK C	ASING USED:		5 Wrought iron		8 Concre	te tile	CASING JOINT	S: Glue	d ^X Clamped
1 Ste		3 RMP (S	R)	6 Asbestos-Ceme			specify below			ed
2 PV		4 ABS	• • •	7 Fiberglass			-	*/ 		aded
			in to 5			in to	,	ft Dia		in. to ft.
Cacina hai	abt above in	and curface	24	in weight	2.77	111, 10	tha !	tt Wall thickness or	raugo M	o 258
-	-	R PERFORATIO		iii., weight :	m,*.*. t	7 PV		•		
				. Partie and a second				10 Asbest		
1 Ste		3 Stainles		5 Fiberglass			P (SR)			
2 Bra		4 Galvaniz		6 Concrete tile		9 ABS	>	12 None i	usea. (op	•
		RATION OPENIN			auzed wi	• •		8 Saw cut		11 None (open hole)
	ntinuous slo		Aill slot		ire wrap	oed		9 Drilled holes		
	uvered shutt		(ey punched		orch cut	0.0				
SCREEN-F	PERFORATE	ED INTERVALS:								:o
										:o
G	RAVEL PAG	CK INTERVALS:	: From			. 80	ft., Fro	m		:o
			From	ft. t	0		ft., Fro	m	ft. t	to ft
GROUT	MATERIAL	: 1 Neat	cement	2 Cement grout		3 Bento	nite 4	Other Bentonit	e Ho	leplug
Grout Inter	vals: Fror	n	.ft. to	ft., From		ft. i	.o	ft., From		ft. to
What is the	e nearest so	urce of possible	contamination:				10 Lives	tock pens	14 A	bandoned water well
1 Se	ptic tank	4 Late	ral lines				•			il well/Gas well
2 Sewer lines 5 Cess							12 Fertilizer storage			Other (specify below)
3 Watertight sewer lines 6 Seepa						13 Insecticide storage .			Pot	nd
Direction for	-	west	5 1	,				ny feet? 100'		
FROM	ТО	<u> </u>	LITHOLOGIC	CLOG	1	FROM	то	PLUC	GING I	NTERVALS
0	15	Topsoil a	ind clay, l	rown						
15	18		own, some g							95, 1199,
18	42			ited sand, ve	ry					
		hard								
42	80		e, soft, ta	an						
		Sandscone	.,,							
									,_,	
			MARKET A			-417				1900/4404
			FINANCIAL PLANE - COLOR - COLO							11 190,00011/10
				·				545 M 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
								W. C.C		A STATE OF THE STA
				V 3.111-2414 4 4 400 V V 7						
	L- nu		** \ *********************************							

							L			
7 CONTE	RACTOR'S	OR LANDOWNE	R'S CERTIFICA	TION: This water we	ell was (1) <u>constr</u> ui	cted, (2) reco	onstructed, or (3) plug	ged un	der my jurisdiction and wa
completed	on (mo/day/	/year)	6-13-91				and this reco	ord is true to the best	of my kn	nowledge and belief. Kansa
								on (mo/dey/yr)7		
under the	hueinaee na	mo of Clark	0 Woll & F	quinment. Inc	,		by (ciana	turo\X / 27 A	1//	