


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 13 Township Number T 12 S Range Number R 18 EW
 County: Ellis

Distance and direction from nearest town or city street address of well if located within city?

7N 2 1/2 E of Hays.

2 WATER WELL OWNER: Kurtis Wolfe
 RR#, St. Address, Box # : 180 Severin Rd. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Hays, KS 67601 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL: 94 ft. ELEVATION: 714 ft.
 Depth(s) Groundwater Encountered 1. 22 ft. 2. 02-08-02 ft.
 WELL'S STATIC WATER LEVEL: 35 TC ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 80 TC ft. after 1 1/2 hours pumping 68 gpm
 Est. Yield 10 to 12 gpm: Well water was 84 TC ft. after 1 1/2 hours pumping 8 gpm
 Bore Hole Diameter: 10 in. to 10 in. and 10 in. to 10 in.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued No Clamped No
 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded No Threaded No
 Blank casing diameter 5 in. to 74 ft., Dia. 5 in. to 74 ft., Dia. 5 in. to 74 ft., Dia. 5 in. to 74 ft., Dia.
 Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. SDR 21
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 94 ft.
 SCREEN-PERFORATED INTERVALS: From 94 ft. to 74 ft., From 94 ft. to 74 ft., From 94 ft. to 74 ft., From 94 ft. to 74 ft.
 GRAVEL PACK INTERVALS: From 94 ft. to 20 ft., From 94 ft. to 20 ft., From 94 ft. to 20 ft., From 94 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other
 Grout Intervals: From 20 ft. to 0 ft., From 20 ft. to 0 ft., From 20 ft. to 0 ft., From 20 ft. to 0 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? east How many feet? 500 ft.

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	loess			
6	10	clay			
10	18	Rock clay - F. sand.			
20	22	Clay			
22	24	clay E. sand			
24	34	clay, limestone Rock			
34	74	sandy clay limestone Rock			
74	84	clay Rock			
84	87	clay Rock			
87	92	weathered shale			
92	94	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02-7-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 608 This Water Well Record was completed on (mo/day/yr) 02-08-02 under the business name of Yellow Truck Only by (signature) Greg Orledy