

1 LOCATION OF WATER WELL: County: OTTAWA	Fraction NW 1/4 NW 1/4 NE 1/4	Section Number 7	Township Number T 12 S	Range Number R 2W E/W
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
308 E. BENNINGTON,

2 WATER WELL OWNER: **NORMAN MANN**
 RR#, St. Address, Box # : **308 E. BENNINGTON, KS.**
 City, State, ZIP Code : **BENNINGTON, KS. 67422**
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

	4 DEPTH OF COMPLETED WELL 34 ft. ELEVATION: Depth(s) Groundwater Encountered 1 18 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 5-24-05 Pump test data: Well water was 25 ft. after 1 hours pumping 25 gpm Est. Yield 25 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7 Domestic (lawn & garden)</u> 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No
--	--

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	
Blank casing diameter 24 5 in. to 24 ft., Dia in. to ft., Dia in. to ft.				

Casing height above land surface **16** in., weight **160** lbs./ft. Wall thickness or gauge No. **SDR 26**

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
SCREEN OR PERFORATION OPENINGS ARE:				

1 Continuous slot	3 Mill slot <u>.025</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From 24 ft. to 34 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 20 ft. to 34 ft., From ft. to ft.				

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From **0** ft. to **20** ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
<u>3 Watertight sewer lines</u>	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? WEST			How many feet? 15	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	FILL DIRT			
2	24	CLAY BROWN			
24	30	SAND FINE TAN			
30	34	IRON STONE AND HARD SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **5-24-05** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **388** This Water Well Record was completed on (mo/day/yr) **5-24-05** under the business name of **PESTINGER PUMP SERVICE** by (signature)