			VVAIER VV	PELL RECORD	FOITH WWW	10-5 NSA 62a	-1212				
LOCATION			Fraction		_	Section Number	Township Nu		1 2	ge Num	\sim
County: 7			1 <u>SE</u> ½S		<u>ا 4/</u>	_ 3 2	1 12	S	R &	メー	E(W)
, , ,	// _		or city street addre	: I			ν				
	12 W			NORTH	07 6	ELLIS A	CS.				
		NER: Eddie	ngng				B		Obstate :	\4/#*	2
		# : RRL	1/2 / 0 / /	- -			Board of A		Division of	Water F	Resources
City, State, Z			Ks 6763		115		Application				
AN "X" IN	NELL'S LO	DCATION WITH 4 D	DEPTH OF COMP	PLETED WELL. er Encountered	13	ft. ELEVA 4 ft. 2	TION:	ft. 3			
<u>,</u>	1	· · · · · w	VELL'S STATIC WA	TER LEVEL	34	ft. below land sur	face measured on	mo/day/yr	12/2	0/9	5
1	1						fter				
	NW	Nt E	st. Yield 10	gpm: Well wa	ater was	ft. af	fter	hours pur	mping		gpm
	;	B	ore Hole Diameter.	/0in. t	ю		and	in.	to	.	ft.
₹ w	1	ı w	VELL WATER TO B	BE USED AS:	5 Public v	water supply	8 Air conditioning	11	Injection w	rell	
7	1		Domestic	3 Feedlot	6 Oil field	water supply	9 Dewatering	12	Other (Spe	ecify bel	ow)
	5W	36	2 Irrigation	4 Industrial	7 Lawn a	nd garden only	10 Monitoring well	. . /			
1 1	;]	i X w	Vas a chemical/bacte	eriological sample	e submitted t	o Department? Ye	esNo	; If yes,	mo/day/yr	sample	was sub-
I	S	m	nitted			Wat	ter Well Disinfected	d? (Yes)	N	lo	
TYPE OF	BLANK C	CASING USED:	5	Wrought iron	8 Cc	oncrete tile	CASING JOIL	NTS: alued	D c	Clamped	
1 Steel		3 RMP (SR)	6	Asbestos-Cemen	nt 9 Ot	her (specify below	v)	Weld	ed		
2 PVC	>	4 ABS		Fiberglass					aded		
			. to								
Casing heigh	nt above la	and surface 28	Š in.,	weight		lbs./1	ft. Wall thickness o	r gauge No	oS.D	R-2	6
TYPE OF SO	CREEN O	R PERFORATION	MATERIAL:		7	PVC	10 Asbe	estos-ceme	ent		
1 Steel	ı	3 Stainless s	iteel 5	Fiberglass	8	RMP (SR)	11 Othe	er (specify)			
2 Brass	S	4 Galvanized	steel 6	Concrete tile	9	ABS	12 None	e used (op	en hole)		
SCREEN OF	R PERFOR	RATION OPENINGS	S ARE:	5 Gai	uzed wrappe	ed	8 Saw cut		11 None	(open h	nole)
1 Conti	inuous slo	t S.Mill	slot	6 Wir	e wrapped		9 Drilled holes				
2 Louv	ered shutt	er 4 Key	punched		ch cut	^	10 Other (specify)			
SCREEN-PE	RFORATE	ED INTERVALS:	From	ft. to	4.	.)ft., Fror	m	ft. te	0		ft.
			From	ft. to		ft., Fror	m				
GR	AVEL PA	CK INTERVALS:	From 2. 5	ft. to	u	ft., Fror	m	ft. te	0		ft.
			From	ft. to		ft., Fror	m	ft. te	0		ft.
6 GROUT N	MATERIAL	: 1 Neat cer	ment 20	enent grout	3 B	entonite 4	Other				
Grout Interva	als: From	m	. to . (2) (2)	. ft., From		ft. to	ft., From		ft. to .		ft.
What is the	nearest so	ource of possible co	ontamination:			10 Livest	tock pens	14 A	bandoned	water w	/el l
1 Septi	ic tank	4 Lateral	lines	7 Pit privy		11 Fuel	storage	15 O	il well/Gas	well	
2 Sewe	er lines	5 Cess p	ool	8 Sewage la	agoon	12 Fertili	zer storage	16 O	ther (speci	ify belov	w)
3 Wate	ertight sew	er lines 6 Seepag	ję pit	9 Feedyard		13 Insec	ticide storage				<i></i>
Direction from	m well?	Vorth A	lorth			How man	ny feet? /00 1				
FROM	TO		LITHOLOGIC LOG	3	FROI		PL	ugging II	NTERVAL	S	
										~~~~~	
0	5	ی مه 7	),[								
5	34	bRown	clay								
34	40	FINE CP	EY San	d							
,		(							and the second second		STATEMENT AND ADDRESS
40	42	beown c	194								
			,								
42	45	COARSE	GREY & RE	d Sand							
		•	1" / [ "	-7							
45	49	549/5									
7 CONTRA	CTOP'S	JB I VIIDOMINED.	S CERTIFICATION:	This water well	was All	etructed (2) reco	enstructed or (3) n	lunged upo	der my juri	sdiction	and was
CONTRA	n (ma/da::	/year) / . 2 / . 2 /	2/95	ino water well	,, as (1) to		ord is true to the be				
			276	This Motor	Mell Poor		on (ma¶day/yr) 🖊:		/ec	iu belle	Nansas
		's License No	Water 4	11/1/	N	was completed to by (signat	u //	0-4	<i>,</i>		
under the bu					11/47			····		2	
INSTRUCT of Health a	IONS: Use ty and Environm	pewriter or ball point per ient, Bureau of Water, To	n. PLEASE PRESS FIRML opeka, Kansas 66620-000	.r and <u>PHINI</u> clearly. 01. Telephone: 913-29	riease illi in bla 6-5545. Send o	inks, underline or circle ne to WATER WELL OV	e me correct answers. So WNER and retain one fo	and top three ryour records	copies to Kar 3.	isas Depa	runent