

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Trego		SE 1/4 SE 1/4 SE 1/4	8	T 12 S	R 21 <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? 2 Miles North 3 Miles East of Ogallah, Kansas					
2 WATER WELL OWNER: Fritz Armbruster					
RR#, St. Address, Box #: RRt					
City, State, ZIP Code: Ellis, Kansas 67637					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 96 ft. ELEVATION: Upland			
		Depth(s) Groundwater Encountered 60 ft. 2. 63 ft. 3. 3/29/89 ft.			
		WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr 3/29/89			
		Pump test data: Well water was 65 ft. after 10 hours pumping 25 gpm			
		Est. Yield 25 gpm: Well water was 65 ft. after 10 hours pumping 25 gpm			
		Bore Hole Diameter 10 in. to 96 ft., and 96 in. to 96 ft.			
WELL WATER TO BE USED AS: 1 5 Public water supply 8 Air conditioning 11 Injection well					
2 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED: 2 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 76 ft., Dia 5 in. to 76 ft., Dia 5 in. to 76 ft.					
Casing height above land surface 24 in., weight 160 lbs./ft. Wall thickness or gauge No. 26					
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 76 ft. to 96 ft., From 76 ft. to 96 ft., From 76 ft. to 96 ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 96 ft., From 24 ft. to 96 ft., From 24 ft. to 96 ft.					
6 GROUT MATERIAL: 1 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 24 ft., From 0 ft. to 24 ft., From 0 ft. to 24 ft.					
What is the nearest source of possible contamination: None					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	8	Clay			
8	16	Sand and Clay			
16	22	Clay			
22	33	Sand			
33	42	Clay			
42	50	Sand			
50	63	Clay			
63	74	Sand			
74	80	Clay			
80	94	White clay			
94	96	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/2/89 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 199 This Water Well Record was completed on (mo/day/yr) 5/25/89					
under the business name of Karst Water Well Drilling & Service Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4