


1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 County: Trego NE 1/4 SE 1/4 SW 1/4 29 T 12 S R 23 #W

Distance and direction from nearest town or city street address of well if located within city?
3315 N and 3185 W of southeast corner of the above.

2 WATER WELL OWNER: City of Wakeeney
 RR#, St. Address, Box # : 408 Russell Ave
 City, State, ZIP Code : Wakeeney, KS 67672
 Board of Agriculture, Division of Water Resources
 Application Number: PW003140

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 103.5 ft. ELEVATION: 2394



Depth(s) Groundwater Encountered 1 54.10 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 54.10 ft. below land surface measured on mo/day/yr 10/3/05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted 8/04
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 PVC 4 ABS 7 Fiberglass cert. - 10k Threaded

Blank casing diameter 16 in. to 71.5 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. 511

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 71.5 ft. to 101.5 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 35.0 ft. to 101.5 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout Bentonite 4 Other
 Grout Intervals: From 0 ft. to 30 ft., From 30 ft. to 35 ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage None Known
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	32	clays			
32	34	gray medium fine sand/trace gravel			
34	58.5	silty clay			
58.5	74	brown sand and gravel/few boulders			
74	79.5	silty sandy clay			
79.5	92	med. coarse sand & gravel with cobbles			
92	94.5	silty clay			
94.5	95	coarse sand/trace of fines			
95	100.5	brown sandy silt			
101.5		yellow brown silt			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/28/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 102 This Water Well Record was completed on (mo/day/yr) under the business name of Layne Christensen Co. by (signature) Russell W Redding