

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: TREGO		NE 1/4 NW 1/4 SE 1/4	5	T 12 S	R 25 E
Distance and direction from nearest town or city street address of well if located within city? BLOCK 22 ANSLIE AVE CULLYER KS					
2 WATER WELL OWNER: TREGO CO HIWAY DEPT - 120 S MAIN WARNEEFY KS. 67672					
RR#, St. Address, Box #: CITY OF CULLYER - CULLYER 67631					
City, State, ZIP Code: Application Number: -					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 2508 + 1 -			
		Depth(s) Groundwater Encountered 1. 71.8 ft. 2. - ft. 3. - ft.			
		WELL'S STATIC WATER LEVEL - ft. below land surface measured on mo/day/yr -			
		Pump test data: Well water was - ft. after - hours pumping - gpm			
		Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm			
		Bore Hole Diameter 7.25 in. to - ft. and - in. to - ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well SOIL BORING			
Was a chemical/bacteriological sample submitted to Department? Yes - No X		If yes, mo/day/yr sample was submitted -			
Water Well Disinfected? Yes - No X					
5 TYPE OF BLANK CASING USED: NA					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped - 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded - Blank casing diameter NA in. to - ft. Dia. - in. to - ft. Dia. - in. to - ft. Casing height above land surface NA in., weight - lbs./ft. Wall thickness or gauge No. - TYPE OF SCREEN OR PERFORATION MATERIAL: NA 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) - 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: NA					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From NA ft. to - ft. From - ft. to - ft. SAND GRAVEL PACK INTERVALS: From 67 ft. to 80 ft. From - ft. to - ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other -					
Grout Intervals: From 3 ft. to 67 ft. From - ft. to - ft. From - ft. to - ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage AREA CONTAMINATED Direction from well? UNDERGROUND STORAGE					
How many feet? UNDERGROUND STORAGE					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	FILL SAND DIESEL ODER			
2	20	SILTY CLAY TAN			
20	40	SILTY CLAY - SANDY			
40	65	SODY CLAY - CALICHE FRAG.			
65	70	CLAY SAND			
70	74.8	SAND - SANDY CLAY			
74.8	80	CALICHE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07-16-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 09-23-92 under the business name of EBBERIS DRILLING by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4