

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: TREGO		NE 1/4 NW 1/4 SE 1/4	5	T 12 S	R 25 EW
Distance and direction from nearest town or city street address of well if located within city? INTERSECTION FOURTH ST AND AINSLIE AVE - COLLYER KS.					
2 WATER WELL OWNER: TREGO CO. HIGHWAY DEPT. 120 S MAIN WAKEENY KS 67672					
RR#, St. Address, Box #: CITY OF COLLYER - COLLYER KS. 67631				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code				Application Number: —	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: —			
		Depth(s) Groundwater Encountered 1. 70.7 ft. 2. — ft. 3. — ft.			
		WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr —			
		Pump test data: Well water was NA ft. after — hours pumping — gpm			
		Est. Yield NA gpm: Well water was — ft. after — hours pumping — gpm			
		Bore Hole Diameter 7.25 in. to — ft., and — in. to — ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well TEMP. MONITORING			
		Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —			
		Water Well Disinfected? Yes — No X			
5 TYPE OF BLANK CASING USED: NA					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped — 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded — Blank casing diameter NA in. to — ft., Dia. — in. to — ft., Dia. — in. to — ft. Casing height above land surface NA in., weight — lbs./ft. Wall thickness or gauge No. — TYPE OF SCREEN OR PERFORATION MATERIAL: NA 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) — 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: NA 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) — SCREEN-PERFORATED INTERVALS: From NA ft. to — ft., From — ft. to — ft., From — ft. to — ft. GRAVEL PACK INTERVALS: From 65 ft. to 80 ft., From — ft. to — ft., From — ft. to — ft. From — ft. to — ft., From — ft. to — ft., From — ft. to — ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other —					
Grout Intervals: From 3 ft. to 65 ft., From — ft. to — ft., From — ft. to — ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) CONTAMINATED Direction from well? AREA - UNDER CO. STORAGE How many feet? —					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.5	ASPHALT			
.5	22	SILTY CLAY			
22	25	SANDY CLAY			
25	29	SAND + GRAVEL			
29	40	SANDY CLAY			
40	44	SAND			
44	55	SILTY CLAY			
55	58	SAND			
58	69.5	SILTY CLAY			
69.5	71	SANDY CLAY			
71	74.8	CLAY SAND - SAND			
74.8	80	CALICHE			
		SAMPLED WATER			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09-28-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 11-02-92 under the business name of EBBERTS DRILLING by (signature) <i>August Ebberts</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4