


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 7 Township Number T 12 S Range Number R 25 E  
 County: RESO

Distance and direction from nearest town or city street address of well if located within city?  
2 miles W Collier

2 WATER WELL OWNER: Leo Pfeiffer  
 RR#, St. Address, Box #: Collier, KS  
 City, State, ZIP Code: Collier, KS  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 106 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 80 ft. 2. 80 ft. 3. 80 ft.  
 WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was 15 gpm. Well water was 9 ft. after 106 hours pumping 106 gpm  
 Est. Yield 15 gpm. Well water was 9 ft. after 106 hours pumping 106 gpm  
 Bore Hole Diameter 9 in. to 106 in. and 106 in. to 106 in.  
 WELL WATER TO BE USED AS:  
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 106 ft. Dia. 106 in. to 106 ft. Dia. 106 in. to 106 ft.  
 Casing height above land surface 12 in. weight 250 lbs./ft. Wall thickness or gauge No. 250  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 0 ft. to 96 ft. From 106 ft. to 106 ft.  
 GRAVEL PACK INTERVALS: From 80 ft. to 106 ft. From 106 ft. to 106 ft.

6 GROUT MATERIAL:  Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 20 ft. From 106 ft. to 106 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy  Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? South How many feet? 300

FROM		TO		LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	8	33	Topsoil			
8	33	33	53	Sandy Clay			
33	53	53	69	M. Shale			
53	69	69	81	Gravel			
69	81	81	90	Fine Sand			
81	90	90	91	Sandy Clay			
90	91	91	102	M. Shale			
91	102	102	106	Sandy Clay			
102	106	106		Chert			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed,  reconstructed, or  plugged under my jurisdiction and was completed on (mo/day/year) 6-8-50 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 376 This Water Well Record was completed on (mo/day/yr) 6-27-50 under the business name of B & B Drilling by (signature) Joseph Beckman

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4