

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ottawa	SW 1/4 SW 1/4 SW 1/4	10	T 12 S	R 3 W

Distance and direction from nearest town or city street address of well if located within city?

3 miles West & 1 mile South of Bennington, KS

2 WATER WELL OWNER:	Dave Stanley	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	350 N. 150th Rd.	Application Number: N/A
City, State, ZIP Code :	Bennington, KS 67422	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 107 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr 11/5/97
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 50 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 110 ft. and in. to ft.
WELL WATER TO BE USED AS:	
<input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
<input type="checkbox"/> Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes. No. <input checked="" type="checkbox"/>; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> . . . Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<input checked="" type="checkbox"/> PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 97 ft., Dia			Threaded
Casing height above land surface 12 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214			
TYPE OF SCREEN OR PERFORATION MATERIAL:		<input checked="" type="checkbox"/> PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut	11 None (open hole)
1 Continuous slot	<input checked="" type="checkbox"/> Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 97 ft. to 107 ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 20 ft. to 107 ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<input checked="" type="checkbox"/> Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft.				
What is the nearest source of possible contamination: none within 1/4 mile		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	14	Brown Clay, sandy			
14	62	Tan Sandstone, soft			
62	75	Blue Shale			
75	107	Tan sandstone, soft			
107	108	Iron pyrite			
108	110	Blue Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (<input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/5/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 11/14/97 under the business name of Peterson Irrigation, Inc. by (signature) <i>Mike Peterson</i>
