

1 LOCATION OF WATER WELL: County: <u>Ottawa</u>	Fraction <u>SW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>24</u>	Township Number <u>T 12 S</u>	Range Number <u>R 3 EW</u>
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?
N. on 9th St. to Buffalo Rd., right to first house on left (Salina)

2 WATER WELL OWNER: <u>George Robertson</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>1711 Buffalo Rd.</u>	Application Number:
City, State, ZIP Code: <u>Bennington, KS 67422</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>58</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: <u>8 7/8</u> in. to <u>58</u> ft., and <u>4 1/2</u> in. to <u>105</u> ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <input checked="" type="checkbox"/> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
<u>2</u> PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter <u>5</u> in. to <u>38</u> ft., Dia			
Casing height above land surface <u>24</u> in., weight			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>7</u> PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<u>3</u> Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>38</u> ft. to <u>58</u> ft., From ft. to ft.		
	From ft. to ft., From ft. to ft.		
GRAVEL PACK INTERVALS:	From <u>29</u> ft. to <u>60</u> ft., From ft. to ft.		
	From ft. to ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3</u> Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>29</u> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	<u>16</u> Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	<u>Unknown</u>

Direction from well?		LITHOLOGIC LOG		PLUGGING INTERVALS	
FROM	TO	FROM	TO	FROM	TO
0	15				
15	40				
40	45				
45	70				
70	105				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/10/00</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>527</u> This Water Well Record was completed on (mo/day/yr) <u>3/22/00</u> under the business name of <u>GeoCore Services, Inc.</u> by (signature) <u>Dale Bell</u>
--