

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: OTTAWA	SW ¼ SW ¼ NW ¼	10	T 12 S	R 3W EW

Distance and direction from nearest town or city street address of well if located within city?
 ¼ MILE NORTH OF ELK RD. AND 150th RD. EAST SIDE OTTAWA COUNTY PERMIT #00-209

2 WATER WELL OWNER: RANDY RADKE
 RR#, St. Address, Box #: 1453 CORONADO RD.
 City, State, ZIP Code: BENNINGTON, KS. 67422
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 101 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 48 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 43 ft. below land surface measured on mo/day/yr 8-23-00
	Pump test data: Well water was 50 ft. after 2 hours pumping 15 gpm
	Est. Yield 60+ gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 9 in. to 101 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued X Clamped
2 PVC	4 ABS	7 Fiberglass		Welded
				Threaded

Blank casing diameter 5 in. to 91 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 24 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot .025	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 91 ft. to 101 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 27 ft. to 48 ft., From 50 ft. to 101 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 27 ft., From 48 ft. to 50 ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	OPEN PASTURE NONE APPARENT

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL			
2	20	CLAY REDISH BROWN			
20	24	CLAY LIGHT BROWN			
24	29	CLAY LIGHT GRAY			
29	44	CLAY DARK GRAY			
44	101	SANDSTONE TAN			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-23-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 388 This Water Well Record was completed on (mo/day/yr) 8-25-00 under the business name of PESTINGER PUMP SERVICE by (signature) Paul Pestinger