


1 LOCATION OF WATER WELL: County: Love Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 20 Township Number: T 12 S Range Number: R 31 E

Distance and direction from nearest town or city street address of well if located within city? 9.5 2W of Campen Ks

2 WATER WELL OWNER: ROD Knapp
 RR#, St. Address, Box #: Orkly, Ks 67748
 City, State, ZIP Code: Orkly, Ks 67748
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 8.5 ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered: 1.55 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 5.5 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 20 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected: Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 5 in. to 6.5 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 1.2 in., weight: 2.50 lbs./ft. Wall thickness or gauge No. 2.50
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 6.5 ft. to 8.5 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 5.5 ft. to 8.5 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Flatland
 13 Insecticide storage
 Direction from well? 0 How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	Top soil			
15	60	clay			
60	83	Gravel			
83	85	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-12 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 326 This Water Well Record was completed on (mo/day/yr) 12-12 under the business name of B+B Orkly, LLC by (signature) Joseph Beckman