WATER WELL RECORD			Form W	WC-5	Division of Water	er Resources App. N	0.	
1 LOCATION OF WATER WELL:			Fraction		Section Number		Range Number	
County: Wallace			⅓ NE ⅓ SE	1/4 SE 1/4	15	T 12 S		
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:								
							(in decimal degrees)	
143' from E line, 680' from S line					Longitude: (in decimal degrees)			
Elevation: WGS 84, NAD 83, NAD 27								
2 WA	TED W	FIT OWNER. W. M.		☐ Datum: ☐ WGS 8	Datum:   WGS 84,   NAD 83,   NAD 27			
2 WATER WELL OWNER: Wyatt Hoss RR#, Street Address, Box #: 2850 Rd 28					Collection Method:  GPS unit (Make/Model:)			
are a man a 1					Digital Map/Photo, Topographic Map, Land Survey			
City	, state, z	. Wallace	KS 67761	Est Accuracy:				
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40 ft.								
SEC'	SECTION BOX: Depth(s) Groundwater Encountered (1)							
	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
	Pump test data: Well water wasft_ after hours pumping gpm							
EST. YIELD gpm. Well water was ft. after hours pumping gpm								
W         E   Bore Hole Diameter 8.5 in. to .40 ft., and								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW. SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☐ No								
S If yes, mo/day/yr sample was submitted								
Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS:  Glued  Clamped  Welded  Threaded								
Casing diameter 4.5 in to 40 ft., Diameter in to ft., Diameter in to ft.								
Casing height above land surface. 18 in., Weight 2.5 lbs/ft., Wall thickness or gauge No. 0.248								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
	Steel	Stainless Steel	<b>₹</b> ] PVC		Other (Specify)			
L.	Brass	☐ Galvanized Steel	☐ None used (open h	ole)				
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 20 ft. to .40 ft., From ft. to ft.								
From								
URAVEL PACA INTERVALO. FIUIL. 14								
From ft. to ft. ft. ft.								
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other								
Grout Intervals: From 0 ft. to 12 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:  Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)  Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
		n well					•••••	
FROM	TO	LITHOLOG		FROM			GGING INTERVALS	
0	2	Surface						
2	13	Loess						
13	18	Fine to med sand w/ so	me gravel					
18	40	Black shale				** #***		
	1							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) 9/14/12 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 838 This Water Well Record was completed on (mo/day/year) 10/19/12								
under the business name of D&R Pump Service, LLC by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, bl	ue, pink) to	Kansas Depar tment of Health	and Environment, Bureau	of Water, Geol	ogy Section, 1000 SW Ja	ckson St., Suite 420,	Topeka, Kansas 666 12-1367.	
Telephone	785-296-	5524. Send one copy to WAT	ER WELL OWNER and r	etain one for	your records. Include <u>fe</u>	e of \$5.00 for each co	enstructed well. Vi sit us at	
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								