

1 LOCATION OF WATER WELL: County: Wallace Fraction: SE 1/4 SE 1/4 NW 1/4 Section Number: 33 Township Number: T 12 S Range Number: R 42 EW

Distance and direction from nearest town or city street address of well if located within city?  
8 miles north of Weskan

2 WATER WELL OWNER: Marion Talbert  
 RR#, St. Address, Box # :  
 City, State, ZIP Code : Cheyenne Wells Co 80810 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 165 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 63 ft. 2. 63 ft. 3. 63 ft.  
 WELL'S STATIC WATER LEVEL 63 ft. below land surface measured on mo/day/yr 8-27-89  
 Pump test data: Well water was 68 ft. after 1 hours pumping 30 gpm  
 Est. Yield 50 gpm: Well water was 68 ft. after 1 hours pumping 30 gpm  
 Bore Hole Diameter 10 in. to 20 ft., and 8 in. to 16.5 ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 1 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes.....No X.....; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 3 in. to 14.5 ft., Dia. 2.81 in. to 21 ft., Dia. 2.81 in. to 21 ft.  
 Casing height above land surface 2 in., weight 200 lbs./ft. Wall thickness or gauge No. 20.5  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 14.5 ft. to 16.5 ft., From 14.5 ft. to 16.5 ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 16.5 ft., From 20 ft. to 16.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 20 ft., From 0 ft. to 20 ft., From 0 ft. to 20 ft., From 0 ft. to 20 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? on site How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	25	clay			
25	30	Rock			
30	45	Sand rock & sand strips			
45	60	Green clay & sand strips			
60	75	Fine sand & red clay			
75	90	Fine sand & red clay			
90	105	Fine sand & red clay			
105	135	sand & clay strips			
135	160	sand & yellow clay			
160	165	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-27-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 213 This Water Well Record was completed on (mo/day/yr) 9-11-89 under the business name of Kemp's Well Service by (signature) George Kemp

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4