

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>OTTAWA</u>	<u>NW 1/4 NW 1/4 NW 1/4</u>	<u>30</u>	<u>T 12 S</u>	<u>R 5W E/W</u>

Distance and direction from nearest town or city street address of well if located within city?
INTERSECTION OF BUFFALO RD. AND LINCHELL RD. SOUTHEAST CORNER

2 WATER WELL OWNER: KENNETH SCHOSHKE
 RR#, St. Address, Box # : 3073 N. BROOKVILLE RD. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : BROOKVILLE, KS. 67425 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

	4 DEPTH OF COMPLETED WELL <u>92</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1 <u>47</u> ft. 2 <u>64</u> ft. 3 ft. WELL'S STATIC WATER LEVEL <u>47</u> ft. below land surface measured on mo/day/yr <u>8-7-02</u> Pump test data: Well water was <u>54</u> ft. after <u>1</u> hours pumping <u>20</u> gpm Est. Yield <u>60+</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 <u>Domestic</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No
--	---

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
2 <u>PVC</u>	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 5 in. to 79 ft., Dia in. to ft.
 Casing height above land surface 24 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 <u>Mill slot .025</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 79 ft. to 92 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 60 ft., From 64 ft. to 92 ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 64 4 Other

Grout intervals: From 0 ft. to 24 ft., From 60 ft. to 64 ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>OPEN PASTURE NONE APPARENT</u>

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL			
2	8	CLAY BROWN			
8	12	SANDSTONE TAN			
12	17	SANDSTONE BROWN			
17	25	CLAY TAN WITH SANDSTONE LAYERS			
25	32	SANDSTONE TAN			
32	64	CLAY GRAY			
64	92	SANDSTONE TAN			
92		SHALE GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-7-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 388 This Water Well Record was completed on (mo/day/yr) 8-7-02 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.