

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Lincoln	SE ¼ NE ¼ NE ¼	6	T 12 S	R 7 EW

Distance and direction from nearest town or city street address of well if located within city?
North Street and Hwy 18, Lincoln, Kansas

2 WATER WELL OWNER: Century Manufacturing RR#, St. Address, Box # : North Street & Hwy 18 City, State, ZIP Code : Lincoln, Kansas 67455	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 74 ft. ELEVATION: 999
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL . . . 15.8 . . . ft. below land surface measured on 4/16/98
	Pump test data: Well water was . . . NA . . . ft. after hours pumping gpm
	Est. Yield . . NA . . . gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter . . . 10 . . . in. to . . . 110 . . . ft., and in. to ft.	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No <input checked="" type="checkbox"/>; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 4 in. to 0 ft. Dia 10 in. to 0 ft. Dia 33 in. to ft.			Threaded. <input checked="" type="checkbox"/>
Casing height above land surface 0 in., weight Sch 40 lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 44 ft. to 74 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 41 ft. to 74 ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 4 ft., From 4 ft. to 41 ft., From ft. to ft.			
What is the nearest source of possible contamination:			
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
			13 Insecticide storage
			14 Abandoned water well
			15 Oil well/Gas well
			16 Other (specify below)
			Unknown
Direction from well? How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Clay, Black			
2	12	Clay, Light Gray			
12	16	Silt, Tan			
16	25	Sand to Coarse Gravel, Tan			
25	31	Sand, Gray			
31	40	Clay to Sandy Clay, Red to Gray			
40	43	Sandstone, Brown to Gray			
43	74	Sand, Tan			
74	77	Sandstone, Brown			
77	110	Clay, Red to Gray			
					MW1, Tag #, Flushmount
					Project Name: Century Manufacturing - BERM
					GeoCore # 542, #

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/16/98 and this record is true to the best of my knowledge and belief.	Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 4/21/98
under the business name of GeoCore Services, Inc.	by (signature) <i>Debra Kobi</i>