CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4) Section-Township-Range changed:
listed as NE NE SE, 13-135-1E
changed to NENESE, 13-135-1W
Other changes: Initial statements: Dickinson County
Changed to: <u>Saline</u> County
Comments:
verification method: well address on form, legal description, position on plat map
city map on internet, and Solomon 1:24,000 topo map. initials: DRL date: 2/28/2001
submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

= *:		WATE	R WELL RECORD	Form WW0	C-5 KSA 82	a-1212		
LOCATION OF W	ATER WELL:	Fraction			Section Number		umber	Range Number
County: Dickir	son	NE 1/4			13	т 13	S	R 1 E
Distance and direction	n from nearest tov	vn or city street a	ddress of well if locate	ed within city	?			_
110 S Popla	r, Solomon,	Ks.						
WATER WELL O	WNER: Solom	on Agri Se	rvices					
ת RR#, St. Address, B	ox # : P.O.E	30x 1725				Board of A	griculture,	Division of Water Resour
City, State, ZIP Code Salina, Ks. 67402					Application Number:			
				30	ft. ELEV	ATION:		
AN "X" IN SECTION	ON BOX:							3
·	``							
† i								ımping gp
NW	NE		•				=	imping gp
1 1 1	!							to
* *	E							
2			O BE USED AS:		ater supply			
sw	. SE	1 Domestic	3 Feedlot				_	Other (Specify below)
	1 1	2 Irrigation	4 Industrial					
		Was a chemical/l	bacteriological sample	submitted to				, mo/day/yr sample was s
<u> </u>	\$	mitted			w	ater Well Disinfecte	d? Yes	No X
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Cor	crete tile	CASING JO	INTS: Glue	d Clamped
1 Steel	3 RMP (SI	R)	6 Asbestos-Cement	9 Oth	er (specify belo	ow)	Weld	led
2 PVC	4 ABS		7 Fiberglass				Threa	aded _X
	er 2	.in. to 18 .	ft., Dia	in.	to	ft., Dia		in. to
								lo. Sch 40
TYPE OF SCREEN			, - 3 -		PVC		estos-ceme	
1 Steel	3 Stainless		5 Fiberglass	8				
2 Brass	4 Galvaniz		6 Concrete tile		ABS		ne used (or	
SCREEN OR PERFO				zed wrapped		8 Saw cut	ie useu (op	11 None (open hole)
				• •				11 None (open noie)
1 Continuous s		lill slot		wrapped		9 Drilled holes	,	
2 Louvered shu		ey punched	7 Torc			` ' '	•	
SCREEN-PERFORA	TED INTERVALS:							to
								to <i>.</i>
GRAVEL P	ACK INTERVALS:	From	. 38 ft. to .	1.6	•			to
		From	ft. to		ft., Fre	om	ft. 1	to
GROUT MATERIA			2 Cement grout					• • • • • • • • • • • • • • • • • • • •
Grout Intervals: Fr	om 16	. ft. to .12.5.(.b	ent)ft., From	125 ft	. to 0(.ce	ementa), From		ft. to
What is the nearest	source of possible	contamination:			10 Live	stock pens	14 A	bandoned water well
1 Septic tank	4 Later	al lines	7 Pit privy		11 Fue	l storage	15 C	Dil well/Gas well
2 Sewer lines	5 Cess	pool	8 Sewage lag	goon	12 Fert	ilizer storage	(16)0	Other (specify below)
	wer lines 6 Seep	age pit	9 Feedyard	•		ecticide storage		ial grain
Direction from well?	At facility	3- F				any feet?		g facility
FROM TO	AC TACTITES	LITHOLOGIC	LOG	FROM			UGGING I	NTERVALS
	Com d mad							
0 3	Sand-med,	-					~ ^	
3 8		ly, siltly, bl				M	v .3	The second secon
8 17		y, sandy, gra	y Drown					
17 26	Silt-sandy							
26 40	Sand-fine t	o coarse						
								A COMMENT OF THE PROPERTY NAMED AND ADDRESS OF THE PROPERTY NAMED ADDRESS OF THE PROPERTY NAMED AND ADDRESS OF THE PROPERTY NAMED AND ADDRESS
							the desired and the state of th	
				-	<u> </u>			
	1							
								der my jurisdiction and w
completed on (mo/da	y/year) 7 . -	·11 - 91						owledge and belief. Kans
Water Well Contracto	• • •							
			This Water \	Well Record	was completed	l on (mo/day/yr)	7-16-9	91
under the business r	or's License No	527	This Water \ es, Inc.	Well Record	was completed by (signa		7-16-9	91
· · · · · · · · · · · · · · · · · · ·	or's License No ame of G	527 GeoCore Servic	es, Inc.		by (sign	ature) Dal	a fol	copies to Kansas Department