

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number				
County: SALINE		SW 1/4 NW 1/4 SE 1/4	12	T 13 S	R 1 EW				
Distance and direction from nearest town or city street address of well if located within city? RT. 1 SOLOMAN, KS.									
2 WATER WELL OWNER: STEVE JANSSEN									
RR#, St. Address, Box # : RT. 1			Board of Agriculture, Division of Water Resources						
City, State, ZIP Code : SOLOMAN, KS 67480			Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION: 1258							
<div style="text-align: center;">N 1 Mile W E S</div> <table border="1" style="margin: auto; text-align: center;"><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE</td></tr></table>		NW	NE	SW	SE	Depth(s) Groundwater Encountered 1. 13 ft. 2. ft. 3. ft.			
		NW	NE						
		SW	SE						
		WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 8-28-89							
		Pump test data: Well water was ft. after hours pumping gpm							
Est. Yield gpm: Well water was ft. after hours pumping gpm									
Bore Hole Diameter 8 in. to ft. and in. to ft.		WELL WATER TO BE USED AS:							
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well							
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped					
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded					
Blank casing diameter 5 in. to ft. Dia in. to ft. Dia in. to ft.		7 Fiberglass		Threaded					
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		7 PVC 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify) 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
		7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well? EAST		How many feet? 15'							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
			29	20	CHLORANATED SAND				
			20	0	CEMENT GROUT				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-28-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 8-28-89 under the business name of PESTINGER PUMP SERVICE by (signature) <i>Steve Janssen</i>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									