

1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 NE 1/4 Section Number 8 Township Number T 13 S Range Number R 10 E
 County: Lincoln

Distance and direction from nearest town or city street address of well if located within city:

3 1/2 south + 3 1/4 west + 1 1/2 South Sylvan grove.

2 WATER WELL OWNER: Steve Hlad
 RR#, St. Address, Box #: R1 245
 City, State, ZIP Code: Sylvan Grove, KS 67481
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 430.8

N	NW	NE	E
X			

WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 4-30-88
 Pump test data: Well water was 24 ft. after 1 hours pumping 5 gpm
 Est. Yield 5 1/2 gpm: Well water was 24 ft. after 1 hours pumping 5 gpm
 Bore Hole Diameter 9 in. to 66 ft. and 66 in. to 66 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected Yes No

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued ☐ Clamped ☐ Welded ☐ Threaded
☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below)
 Blank casing diameter 5 in. to 33 ft., Dia. 33 in. to 33 ft., Dia. 33 in. to 33 ft., Dia. 33 in. to 33 ft., Dia.
 Casing height above land surface 12 in., weight 33 lbs./ft. Wall thickness or gauge No. SAR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 11 Other (specify)
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☒ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 33 ft. to 66 ft., From 33 ft. to 66 ft., From 33 ft. to 66 ft., From 33 ft. to 66 ft.
 GRAVEL PACK INTERVALS: From 32 ft. to 66 ft., From 32 ft. to 66 ft., From 32 ft. to 66 ft., From 32 ft. to 66 ft.

6 GROUT MATERIAL: Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other C 1/4 X BACK FILL
 Grout intervals: From 0 ft. to 20 ft., From 20 ft. to 32 ft., From 32 ft. to 20 ft., From 32 ft. to 20 ft.

What is the nearest source of possible contamination:
☐ 1 Septic tank ☒ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage

Direction from well? 50 How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	TOP SOIL			
3	28	BROWN CLAY			
28	32	SAND & ROCK			
32	47	SAND - coarse			
47	53	SAND CLAY brown			
53	59	SAND FINE medium clay			
59	62	grey clay			
62	66	light tan clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-30-88 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 485 This Water Well Record was completed on (mo/day/yr) 4-30-88
 under the business name of RUSHALL WATER WELL DRILLING by (signature) Lois Rushall

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.