		WATER	WELL RECORD	Form W	WC-5 KSA	82a-12	12			mu	,-11	
1 LOCATION OF WAT	ER WELL:	Fraction	Ctri	NT. 7	Section Nun	nber		Number	R	ange Nu	mber	
County: Distance and direction	from poarast town o	NW 1/4	SW 1/4	NW 1/4	27		Т	<u>13 s</u>	R	18	<u> </u>	
	E corner of				oity :							
2 WATER WELL OW	NER:		, , , , , , , , , , , , , , , , , , , ,									
RR#, St. Address, Box	# C.W. Lame	r					Board o	of Agriculture,	Division	of Water	Resource	
City, State, ZIP Code	3509 Chaur	mont Drive	, Hays, Ks	67601				tion Number:				
LOCATE WELL'S LO	CATION WITH 4	DEPTH OF CO	MPLETED WELL.	. 35	ft. EL	EVATIO	N:	 .				
AN "X" IN SECTION	De De	pth(s) Groundwa	ater Encountered	1. 2.1.		. ft. 2	. 	ft. 3	3 -		ft.	
ĭ !	ı Wi	ELL'S STATIC V	VATER LEVEL	26.41	ft. below land	d surface	e measured	on mo/day/yr	9/13	3/95		
NW	NE		est data: Well w									
1 'i'			gpm: Well w									
M 1	ti		8,625 in									
_		ELL WATER TO 1 Domestic	3 Feedlot		water supply		Air condition	ing 11 12	Injection		dow)	
sw	SE	2 Irrigation	4 Industrial		d water suppl and garden or			vell Mu	7 -11	specify be	eiow)	
		-	cteriological samp							/vr sampl	e was sub	
<u>t</u>		tted	otoriological barrip	io dadiminod				cted? Yes				
5 TYPE OF BLANK C			5 Wrought iron	8 C	Concrete tile			JOINTS: Glue				
1 Steel	3 RMP (SR)	(6 Asbestos-Ceme	nt 9 C	Other (specify	below)		Weld	ded	<u>.</u>		
2 PVC	4 ABS	0.0	7 Fiberglass					Thre	aded y	ξ		
Blank casing diameter	2 in.	to . 20	ft., Dia	mater i	n. to 	· · · ·	.ft., Dia		in. to .	· · · ·	ft.	
Casing height above la	nd surface	ir	n., weight		A-1	ibs./ft. V	Vall thicknes	ss or gauge N	10			
TYPE OF SCREEN OF				_	7 PVC			Asbestos-cem				
1 Steel	3 Stainless st		5 Fiberglass		8 RMP (SR)			Other (specify)				
2 Brass SCREEN OR PERFOR	4 Galvanized		6 Concrete tile	: uzed wrapp	9 ABS	۵	Saw cut	None used (or		ne (open	hole)	
1 Continuous slot	^			re wrapped	6 0		Drilled hole	ve	II NO	ne (open	riole)	
2 Louvered shutte				rch cut				cify)				
SCREEN-PERFORATE	• •) ft. to	3	5 ft.,							
SANP		From	 ft. to	سزخة	<u>.</u> ft.,	From .		ft. ·	to <u></u>		ft.	
-GRAVEL PAC	CK INTERVALS:	From 1.7	ft. to	, <i>5</i> 5	? ft.,			ft. '				
		From	ft. to	~~		, From		ft. ·			ft.	
6 GROUT MATERIAL:	Neat cem		Cement grout			- 7						
			π., From	· /		. k _ivestock		14.4		ed water v		
What is the nearest so	urce of possible cor 4 Lateral li		7 Pit privy		_				Dil well/G		Weil	
2 Sewer lines 5 Cess pool			8 Sewage I		11 Fuel storage12 Fertilizer storage			16 Other (specify below)				
	er lines 6 Seepage		9 Feedyard	-			le storage			_		
Direction from well?	-	•				many f	•	Contam	unate	a Si		
FROM TO		LITHOLOGIC LO	OG	FRC	м то			PLUGGING	INTERVA	ALS		
		-				_						
GL 0.50	Soil						<u> </u>					
0.50 27.00	Silty Clay	(CL)							·			
27.00 35.00	Sandy Silt	• •										
35.00 TD	End of bor	ehole -										
						Flush Mount						
						waiver D.Taylor						
						P.1	ayror	- Like West C				
			enter of the second second second second second second	,								
				-	_							
7 CONTRACTOR'S C												
completed on (mo/day/	year) 4/9;	/96 · · · · ·		· · · · · · · · · · · · · · · · · · ·				best of my kr	iowledge	and belie	er. Kansas V	
Water Well Contractor's			This Water			eted on (signature			4/17/		~• 	
under the business nar	MSSOCIA	ted Enviro	nmental, In	Please fin to t	7 1		· · · · · ·				artmost	
	pewriter or ball point pen.									nansas Dep	arti i i i i i i i i	