


1 LOCATION OF WATER WELL: County: Ellis Fraction: NE 1/4 SE 1/4 SW 1/4 Section Number: 33 Township Number: T 13 S Range Number: R 18 EW

Distance and direction from nearest town or city street address of well if located within city?  
Don's 66 1302 Main Hays, Ks. 67601

2 WATER WELL OWNER: Dan & Carol Scheck  
 RR#, St. Address, Box #: 1302 Main Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Hays, KS. 67601 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 30' ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 19' ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 18:10 ft. below land surface measured on mo/day/yr 2-18-94  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 7 1/2" in. to 30' ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded X  
 Blank casing diameter 2.375 in. to 15' ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface: Flush Ground weight lbs./ft. Wall thickness or gauge No. SDR 13  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement SCH 40  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 30' ft. to 15' ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 30' ft. to 13' ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 13' ft. to 4' ft., From 4' ft. to 0 ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage Fouler 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? West How many feet? 30'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Asphalt			
.50	6.50	Dk. - med. brn silty clay, moist to dry. Earthy odor, semi friable.			
6.50	10.50	Tanish brn silty clay, moist to dry. caliche stringers (very thin) no odor.			
10.50	17	Gray brn - lt brn clayey silt to silty clay. moist, iron oxide staining. Dk gray to blk banding at 12-13' through 17', no odor.			
17	19.50	Gray green sandy silt, moist to wet, no odor.			
19.50	25	Fine coarsed grained sand & gravel, wet, subrounded.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-18-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 2-26-94 under the business name of JB Environmental Drilling by (signature) James Bieber

OFFICE USE ONLY

T

R

EW

SEC

1/4

1/4

1/4