

1 LOCATION OF WATER WELL: County: Ellis		Fraction NE 1/4 SE 1/4 SW 1/4		Section Number 33		Township Number T 13 S		Range Number R 18 EW	
Distance and direction from nearest town or city street address of well if located within city? Don's 66 1302 Main Hays, Ks. 67601									
2 WATER WELL OWNER: Dan & Carol Scheck RR#, St. Address, Box # : 1302 Main City, State, ZIP Code : Hays, KS. 67601						Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: 30' ft. ELEVATION: Depth(s) Groundwater Encountered 1. 19' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 20.75 ft. below land surface measured on mo/day/yr 2-18-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/2 in. to 30' ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2.375 in. to 15' ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface Flush Mount in., weight lbs./ft. Wall thickness or gauge No. SDR 13 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement SCH 40 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 30' ft. to 15' ft., From ft. to ft. GRAVEL PACK INTERVALS: From 30' ft. to 13' ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 13' ft. to 5' ft., From 5' ft. to 0' ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? North East How many feet? 200'									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 .50 Concrete									
.50 3.50 Dk. brn clay, tight, no odor.									
3.50 14.50 Med tan brn silty clay, moist, no odor, slight caliche stringers, friable.									
14.50 17 Med- dk. brn silty clay, moist, friable, no odor.									
17 19 Lt. brn sandy silt, moist no odor, soft.									
19 30 Fine coarsed grained sand, dry, loose, no odor, subrounded.									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-18-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 2-26-94 under the business name of JB Environmental Drilling by (signature) James Burke									