


1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 NW 1/4 Section Number 34 Township Number T 13 S Range Number R 18 **EW**

Distance and direction from nearest town or city street address of well if located within city?
 2506 Vine, Hays, Ks.

2 WATER WELL OWNER: Love's Country Store
 RR#, St. Address, Box #: 2506 Vine Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Hays, Ks. Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 63 ft. ELEVATION: ...
 Depth(s) Groundwater Encountered 1. 5.4 ft. 2. ... ft. 3. ... ft.
 WELL'S STATIC WATER LEVEL: 54.5 ft. below land surface measured on mo/day/yr 1.2-13-90
 Pump test data: Well water was ... ft. after ... hours pumping ... gpm
 Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter: 7.5/8 in. to 6.3 ft., and ... in. to ... ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only **10 Monitoring well**
 Was a chemical/bacteriological sample submitted to Department? Yes...No...
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 2 in. to 4.8 ft., Dia. in. to ... ft., Dia. in. to ... ft.
 Casing height above land surface: 0 in., weight ... lbs./ft. Wall thickness or gauge No. Sch. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass **7 PVC** 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot **3 Mill slot** 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 6.3 ft. to 4.8 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From 6.3 ft. to 4.7.5 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement **2 Cement grout** **3 Bentonite** 4 Other
 Grout intervals: From 4.7.5 ft. to 44.5 (bent.) From 44.5 ft. to 0 (cement) From ... ft. to ... ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage **16 Other** (specify below)
 13 Insecticide storage **Underground fuel storage tanks**
 Direction from well? West How many feet? 30

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.5	Asphalt			
.5	15	Clay - silty, brown			
15	35	Clay - silty, brown, caliche pebbles			
35	54	Clay - silty, sandy, very fine, brown			MW# 2
54	61	Sand - fine to med, clayey gray and or green			Completed at the surface with a locking, watertight cap and bolt down manhole cover.
61	63	Shale - dk. gray, black			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1) constructed**, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1.2-13-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527. This Water Well Record was completed on (mo/day/yr) 4-18-91 under the business name of **GeoCore Services, Inc.** by (signature) *Dale A. Bell*