


1 LOCATION OF WATER WELL: County: ELLIS Fraction: SW 1/4 SE 1/4 SW 1/4 Section Number: 35 Township Number: T 13 S Range Number: R 18 EW

Distance and direction from nearest town or city street address of well if located within city?  
1325 Agnes Haus Ks. 67601

2 WATER WELL OWNER: Jay Weigle  
 RR#, St. Address, Box #: 1325 Agnes  
 City, State, ZIP Code: Hays Ks 67601  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 53 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 35 ft. 2. . ft. 3. . ft.  
 WELL'S STATIC WATER LEVEL: 31 ft. below land surface measured on mo/day/yr 5/24/84  
 Pump test data: Well water was 22 ft. after 1 1/2 hours pumping 20 gpm  
 Est. Yield 20 gpm: Well water was . ft. after . hours pumping . gpm  
 Bore Hole Diameter: 10 in. to . ft., and . in. to . ft.  
 WELL WATER TO BE USED AS:  
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes . No . If yes, mo/day/yr sample was submitted .  
 Water Well Disinfected:  Yes  No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS:  Glued  Clamped  
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded .  
 7 Fiberglass Threaded .  
 Blank casing diameter: 5 in. to . ft., Dia. . in. to . ft., Dia. . in. to . ft.  
 Casing height above land surface: 24 in., weight . lbs./ft. Wall thickness or gauge No. SDR 21  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) .  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) .  
 SCREEN-PERFORATED INTERVALS: From 33 ft. to 53 ft. From . ft. to . ft.  
 From . ft. to . ft. From . ft. to . ft.  
 GRAVEL PACK INTERVALS: From 25 ft. to 53 ft. From . ft. to . ft.  
 From . ft. to . ft. From . ft. to . ft.

6 GROUT MATERIAL:  Neat cement 2 Cement grout 3 Bentonite 4 Other .  
 Grout Intervals: From 5 ft. to 15 ft. From . ft. to . ft. From . ft. to . ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage .  
 Direction from well? South How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10	top soil			
10	35	brown clay			
35	49	coarse to med red & clear sand			
49	53	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed,  reconstructed, or  plugged under my jurisdiction and was completed on (mo/day/year) 5/24/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 026 This Water Well Record was completed on (mo/day/yr) 5/24/84 under the business name of HUSA Water Well Drilling by (signature) John Green

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4