


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 28 Township Number T 13 S Range Number R 18 E
 County: Ellis

Distance and direction from nearest town or city street address of well if located within city?
501 W 27th Street, Hays Ks MW-7

2 WATER WELL OWNER: CME 2502
 RR#, St. Address, Box # : 2 N. Nevada Board of Agriculture, Division of Water Resource
 City, State, ZIP Code : Colorado Springs, Co 80903 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 59 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 40 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 42.55 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded X
 Blank casing diameter 4" in. to 30 ft., Dia in. to ft., Dia in. to f
 Casing height above land surface 0 in., weight lbs./ft. Wall thickness or guage No. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) f
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From ft. to f
 From ft. to ft., From ft. to f
 GRAVEL PACK INTERVALS: From 28 ft. to 50 ft., From ft. to f
 From ft. to ft., From ft. to f

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 26 ft., From 26 ft. to 28 ft., From ft. to f
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? EAST How many feet? 100'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4"	Concrete			
4"	6'	Clay, dk brn, calc, damp			
6'	10'	Clay, brn, Finu-silt, tr silt, damp			
10'	20'	Clay, brn, soft, v. silt, damp			
20	25	Clay, lt brn, soft, v silt, damp			
25	32'	Sand, lt brn, F-M, tr calc, damp			
32	33	Sand, lt brn, clayey, m-c, dry			
33	50	Sand, lt brn, F-C, damp - sat @ 38			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and wa
 completed on (mo/day/year) 11-17-04 and this record is true to the best of my knowledge and belief. Kansa
 Water Well Contractor's Licence No 705 This Water Well Record was completed on (mo/day/yr) 12-9-04
 under the business name of HANDEX by (signature) [Signature]