


1 LOCATION OF WATER WELL: County: <u>Ellis</u>	Fraction <u>SE 1/4 SE 1/4 SE 1/4</u>	Section Number <u>28</u>	Township Number T <u>13</u> S	Range Number R <u>18</u> E <u>10</u>
---	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

45' West of 2701 Vine Street Hays KS

2 WATER WELL OWNER: Verlin Pfannenstiel
 RR#, St. Address, Box # : P.O. Box 39
 City, State, ZIP Code : Hays KS 67601
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <u>20.0</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered <u>1 NA</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>NA</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>NA</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well <u>SU-SS</u>
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>	

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS
 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass
 8 Concrete tile 9 Other (specify below)
 CASING JOINTS: Glued Clamped
 Welded
 Threaded X
 Blank casing diameter 2.375 in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface -0.3 By 5 in., weight 0.70 lbs./ft. Wall thickness or gauge No. 24.40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 3 Mill slot 0.040 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 20.0 ft. to 10.0 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20.0 ft. to 9.1 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 9.1 ft. to 6.5 ft., From 6.5 ft. to 1.2 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet? 15'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>0.5</u>	<u>Concrete</u>			
<u>0.5</u>	<u>20</u>	<u>Clay to Silty Clay Dk grey Brn</u> <u>↑ Plasticity / firm / moist</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/14/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 735 This Water Well Record was completed on (mo/day/yr) 1/4/05 under the business name of MICO by (signature) Jan P. Pottor