

1 LOCATION OF WATER WELL: County: Ellis	Fraction NW ¼ NW ¼ NW ¼	Section Number 34	Township Number T 13 S	Range Number R18 E
---	-----------------------------------	-----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?
2601 Vine - Hays Kansas

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	KDHE-BER 1000 Jackson Sw - Suite 400 Topeka, KS 66612	Board of Agriculture, Division of Water Resources Application Number: AS-3
---	--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 68 ft. ELEVATION: 2037.32 ft.
--	---

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL **55.45** ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) **10** Monitoring well **AS-3**

Was a chemical/bacteriological sample submitted to Department? Yes No **X**; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No **X**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
<input checked="" type="checkbox"/> 1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
<input checked="" type="checkbox"/> PVC	7 Fiberglass		Threaded X
3 RMP (SR)			
4 ABS			
Blank casing diameter 2 in. to 63 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 0 in., weight 0.70 lbs./ft. Wall thickness or gauge No. 0.154			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<input checked="" type="checkbox"/> PVC	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot 0.020			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 63 ft. to 68 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	<input checked="" type="checkbox"/> Cement grout	<input checked="" type="checkbox"/> Bentonite	4 Other
Grout Intervals: From 0 ft. to 2 ft., From 2 ft. to 63 ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below) Contaminated site
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.5	Asphalt			
.5	11	Fill, silty w/sand & gravel			
11	15	Silt			
15	25	Sand			
25	30	Silt, dk brown-green			
30	35	Silt, dk brown			
35	40	Silt			
40	55	Silts, dk grey			
55	63	Silts with clay			
63	66	Sand			
66	69	Sand and gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-02-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 554 This Water Well Record was completed on (mo/day/yr) 10-5-95 under the business name of Woofter Pump & Well Inc by (signature) <i>Paul Woofter</i>
