1 LOCATI	ION OF WAT	ER WELL:		ER WELL REC	ORD For		KSA 82a tion Numb		Number	Range Num	ber
County: Ellis			NE 1/4	NE 3	4 SW		33	T 13		R 18	w
	nd direction fr	om nearest to	own or city street ad	dress of well 16 th and N	if located wi	thin city?	Kanese				
2 WATER	WELL OWN	FR: City	of Havs	10 and w	iaiii ou ce	i, mays,	Namede				
			Vine Street					Board of A	griculture, Divi	sion of Water Re	sources
City Ctata	ZID Codo	· Have	Ks 67601					Application	Number		
3 LOCATE	E WELL'S LO	CATON WIT	Depth(s) Ground	OMDI ETED	WELL	33	4 FI	EVATION:			
- AN A !	NOLOTION	DOX.	Depth(s) Ground	water Encour	ntered 11.5	95	16. EE	ft. 2	ft.	3	Ft. S
	N		WELL'S STATIC	WATER LEV	EL 2	5.65 ft.	below land	d surface measure	ed on mo/day/	yr 07/03/	Ft. 5
А Г	- T	i						Ft. after			Gpm
	NW - -	NE	Est. Yield	Gpm:	Well water	was		Ft. after	Hours	oumping	Gpm 0
	i	i	Bore Hole Diame WELL WATER T 1 Domestic	ter 8.62	5 In. to	33	3	ft. and	in	. to	Ft.
ê W L	+ x		E WELL WATER T	OBE USED A	AS: 5 Pu t 6 Oil	blic water si field water:	upply supply	8 Air cond 9 Dewater	tioning 1 ina 1:	1 Injection well 2 Other (Specify	l →
1			2 Irrigation	4 Industri	al 7 Lav	wn and gard	den (dome:	stic) 10 Monitor	ing well	IW-3	
	sw - -	SE						t? Yes No			e was
			Submitted	-				Vater Well Disinfe			
5 TYPE O	F BLANK Ĉ	SING USED:		5 Wrough	t Iron	8 Concre	ete tile	CASING J	OINTS: Glue	d Clampe	ed
1 St	eel	3 RMF	P (SR)	6 Asbesto	s-Cement	9 Other	(specify be	elow)	Weld		
2 PV	/C	4 ABS	i	7 Fibergla	iss			L	Threa	aded X	
Blank casin	n diameter	2	in. to 17.	Ft., 5 Dia		In. t	0	ft Dia		in. to	ft.
Casing heig	ht above lan	d surface	in. to 17.	In., weight	SC	H 40	Lbs.	ft. Wall thickness	or gauge No		
TYPE OF S	CREEN OR	PERFORATION	ON MATERIAL:	, 0		7	PVC	10 A	sbestos-ceme	nt	
1 Ste	eel			5 Fibergla		8	RMP (SR)	11 0	ther (specify)		
2 Bra	ass OR PERFORA		anized steel	6 Concret		9	ABS	12 N	one used (ope	en hole) 11 None (open	
	ntinuous slot		Mill slot		6 Wire w			9 Drilled hol		11 None (open	fiole)
	uvered shutte		Key punched		7 Torch	cut		10 Other (sp	ecify)		
SCREEN-P	ERFORATE	INTERVAL:	S: From	17.5 ft	t. to	32.5	ft.	From	ft. t	0	ft.
			From	ft	. to		ft.	From	ft. t	0	Ft. 3
SAI	ND PACK IN	TERVALS:	From		. to	33	ft.	From	ft. t		
			From	ft	t. to		ft.	From		0	
6 GROUT	MATERIAL:	1 Nea	t cement 2	Cement grou	ıt_]	3 Ben	tonite	4 Other			
Grout Interv	als From3	14.5	ft. to 16.5	From2	0	to	14	1.5 ft. From		ft. to	ft.
What is the	nearest sour	ce of possible	e contamination:					estock pens			ell
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well											
	wer lines		5 Cess pool		Sewage la	agoon		tilizer storage		er (specify below)	
Direction fro	atertight sewe	rlines	6 Seepage pit	9	Feedyard		How mar	ecticide storage	Co	ntaminated S	oite
FROM	ТО	CODE	LITHOL	OGIC LOG		FROM	ТО		LUGGING IN	TERVALS	
0	1.5	S	oil, brown, sil	t loam							<u></u>
1.5	11.5		ilty Clay (CL)								
11.5 14.5	14.5 24		ilty Sand (SM) ilty Clay (CL)	,						· · · · · · · · · · · · · · · · · · ·	
24	33		and (SW)								
33	TD		nd of Borehol	е							
·											
									79.		
7 CONTRA	ACTOR'S OR	LANDOWNE	ER'S CERTIFICATION	ON: This water	er well was	(x) construc	ted, (2) red	constructed, or (3)	plugged und	er my jurisdiction	and w
	on (mo/day/yr		06/28	3/06		And thi		true to the best o			- 1
		icense No.		585		This W	ater Well F	Record was comp	eted on (mo/d	lay/yr) 07/2	
			Associate	ed Enviro	nmental	, Inc.		_			
INSTRI	UCTIONS:. Pl	ease fill in blan	nks and circle the corre	ect answers. S	end three co	pies to Kansa -R and retair	as Departmo	ent of Health and E	wironment Bu	reau of Water, Tope	eka,