VATER WELL RECORD Form WWC-5	(SA 82a-1212	D No.	SVE-19
------------------------------	--------------	-------	--------

1 LOCATION OF WATER WELL:	Fraction			Secti	on Number	Township Nu	mber	Range N	lumber
	SE 1/4	SW 1/4	SW y	1	28	т 13	S		
Distance and direction from nearest tow	n or city street add	ress of well if				4			
501 W 27 th Street, Hays,KS	•								
2 WATER WELL OWNER: Coasta	I Mart #2502								
RR#, St. Address, Box # : 2 N Ne						Board of Agricu	ılture. Divi	ision of Water	Resources
City State 7IP Code · Colora	do Sprinas. (CO 80903				Application Nu			10000
3 LOCATE WELL'S LOCATON WITH									
AN "X" IN SECTION BOX:	DEPTH OF C	OMPLETED \	WELL	30	ft. ELEV	/ATION:			
N	Depth(s) Groundy	vater Encoun	tered 1		ft.	. 2	ft.	3	ft.
4 X	WELL'S STATIC	WATER LEV	EL NA	ft. t	elow land s	urface measured o	n mo/day/	vr	
						t. after			
NWNE									
	Est. Held	ypiii. \	veli water was	30		t. after	110015 L	Jumping	gpin
₩ W E	Bore Hole Diame	er ileciń.	เท. เง งระ ธ ยืนได้เลื่อ	JU Water cu	nnly	ft. and 8 Air condition 9 Dewatering	inaIr	1. IO 1. Injection we	π.
	1 Domestic	3 Feed lot	6 Oil fiel	d water s	upply	9 Dewatering	"" ^y (1	Other (Spec	cify below)
SW SE	2 Irrigation	4 industria	i 7 Lawn	and garde	en (domestic	c) 10 Monitoring	well	Soil Vaper E	xtraction
						Yes No			
S	submitted					ter Well Disinfected			
	Isabilitea	E 10/		C					
5 TYPE OF BLANK CASING USED:	(CD)	5 Wrought				CASING JOIN			
Steel 3 RMP (s-Cement 9	Other (specify belo	w)	Weld	led	
2 PVC 4 ABS		7 Fibergla	ss				Thre	aded	.X
Blank casing diameter 4	in. to 15	ft., Dia		in. to)	ft., Dia		in. to	ft.
Casing height above land surface	0	n., weight	.71	6	lbs./ft.	Wall thickness or g	gauge No.	.1.	54
TYPE OF SCREEN OR PERFORATIO	N MATERIAL;			3	PVC	10 Asbe	stos-ceme	ent	
1 Steel 3 Stainle	ess steel	5 Fibergla	SS	8	RMP (SR)	11 Other	r (specify)		
1						12 None			
SCREEN OR PERFORATION OPENIN								11 None (or	en hole)
1 Continuous slot 3	Mill slot		6 Wire wrap	ped		9 Drilled holes			1
2 Louvered shutter 4	Key punched		7 Torch cut			10 Other (speci	fy)		
SCREEN-PERFORATED INTERVALS	From	15 ្មា	. to	30		rom	ft.	to	ft.
	From	ft	. to		ft. F	rom	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	2.5 ft	. to	30	ft. F	rom	ft.	to	ft.
	From					rom			ft.
6 GROUT MATERIAL: 1 Neat									
Grout Intervals From 0	8 to 12 5	& From		<u>5 Dem</u>	OTHE	4 Other		A 40	Δ
Note in the account course of security	N. IO	IL. FIOR		11. 11	40 15	II. FIUIII			
What is the nearest source of possible		_	Dit			tock pens		andoned water	
1	4 Lateral lines					storage		well/ Gas wel	
2 Sewer lines	5 Cess pool		Sewage lago			izer storage		her (specify be	
3 Watertight sewer lines	6 Seepage pit	9	Feedyard		13 Insec	ticide storage	Co	ntaminate	d Site
Direction from well?						feet?			
FROM TO CODE		OGIC LOG		FROM	то	PLU	IGGING II	NTERVALS	
0 5 Sa	ndy Clay Soi	l							
	ay, Silty	5 a m -1			ļl			,	
10 15 CI	ay to Clayey	Sand			ļ				
	nd, Slightly (layey							
20 30 Sa	ınd								
					 				
					 				
					1				
<u> </u>									
					 				
					ļl			· · · · · · · · · · · · · · · · · · ·	
					ļ				
7 1001 170 100 100 100 100 100 100 100 1	DIO OFFICIAL	ON. ***			1	- A			
7 CONTRACTOR'S OR LANDOWNE			er weii was (<u>1)</u>						
	06-1					rue to the best of m	•	-	
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 10-02-07									
under the business name of	Wooft		& Well Inc.		b	y (signature)	tau 1	- Word	
INSTRUCTIONS: Please fill in blank	s and circle the com	ect answers. S	end three copie	s to Kansa	s Departmen	nt of Health and Envir	onment, B	ureau of Water,	1000 S W
Jackson St., Ste. 420, Topeka, Kansa	98 66612-1367. Tele	pnone: 913-29	96-5545. Send	one to WA	TER WELL	OWNER and retain or	ne for your	records.	