<u>82</u>
8

									Re	Moc	1)
1 LOCATI	ON OF WATE	R WELL:	Fraction	ER WELL RECO	ORD For		KSA 82a-1 tion Number		Number	Range N	lumber
	E			NW ½	SE			T 13			8 w
Distance an	nd direction fro	om neares	t town or city street a	ddress of well it	f located wi	thin city?				1	
					ast of U.	S Highwa	ay 40				
			t Hays State Ui	niversity							
RR#, St. Ad	dress; Box#	: 600	Park Street					Board of A	griculture, Divi	ision of Water	Resources
	ZIP Code	: Hay	rs, KS 67601					Application	Number:		
3 LOCATE	E WELL'S LO	CATON W	4 DEPTH OF	COMPLETED	WELL	25	ft. ELEV	VATION:			
	., 020, 101, 1		Depth(s) Groun	dwater Encoun	tered 1	17	ft	. 2	Ft.	3	Ft.
	N		WELL'S STATION	WATER LEV	EL 18	3.27 ft.	below land s	surface measure	ed on mo/day/	vr 10/1/20	09
			_ 1					t. after			
		į	Est. Yield								
 -	NW	NE	Bore Hole Diam	eter 6.825	In to	2	 5	ft and	in	n. to	Ft.
₩ W	- ' - 	1	Bore Hole Diam WELL WATER 1 Domesti	TO BE USED A	\S: 5 Pu	blic water s	upply	8 Air cond	itioning 1	1 Injection we	ii
- "			1 Domesti	c 3 Feed lot	6 Oil	field water	supply	9 Dewater	ing 12	2 Other (Spec	cify below)
	SW/ X	SE	2 Irrigation	1 4 Industria	al 7 Lav	wn and gard	den (domesti	c) 10 Monito	ring well	/IVV-10	
	-	; i	Was a chemical	/bacteriologica	l sample su	bmitted to	Department?	Yes No	X If yes.	mo/day/yr sai	mple was
† L	!	!	Submitted	-0.34	, - 3-			iter Well Disinfe			
5 TYPE O	F BLANK CAS	SING USE		5 Wrought	t Iron	8 Concr		CASING J			mped
1 Ste			MP (SR)							ed	
2 PV		7 4 AE		7 Fibergla						aded	X
		_		F 4							
Blank casing	g diameter	2	in. to 15	Dia		In.	to	ft., Dia		in. to	Ft.
Casing heig	tht above land	surface	FLUSH	In., weight	SC	H 40	Lbs./ft.	Wall thickness	s or gauge No.		
		PERFORA	TION MATERIAL:			7	PVC	10 A	sbestos-ceme	ent	- 1
1 Ste	eel	3 St	ainless steel	5 Fibergla	ss	8	RMP (SR)	11 0	ther (specify)		
2 Bra			alvanized steel					12 N	one used (ope	en hole)	
										11 None (op	en noie)
			3 Mill slot		6 Wire w			9 Drilled hol			
			4 Key punched		7 Torch o			10 Other (sp	ecity)		
SCREEN-P	ERFORATED	INTERVA	ALS: From	π	. to	25	π	-rom	π. υ		·"
				π	. 10	25		rom			
SAI	ND PACK INT	EKVALS:				25			ft. t		۲۰. Ft.
6		4.11	From		. to	0.0		rom			
GROUT	MATERIAL:	7 Ne	eat cement 2	Ft.	τ	S Ben					I
Grout Interv	als From3	12	ft. to 14	From2	0	to	12	ft. From	1	ft. to	ft.
			ble contamination:					tock pens	14 Aba	andoned water	well
1 Sep	ptic tank		4 Lateral lines	7	Pit privy		11 Fuels	storage	15 <u>Oil</u>	well/ Gas well	
2 Sev	wer lines		5 Cess pool	8	Sewage la	agoon	12 Fertili	zer storage	16 Oth	ner (specify be	low)
3 Wa	tertight sewer	lines	6 Seepage pit	9	Feedyard		13 Insec	ticide storage	Co	ntaminate	d Site
Direction fro	m well?						How many	feet?			
FROM	то	CODE	LITHO	LOGIC LOG		FROM	то	F	PLUGGING IN	TERVALS	
0	.5		Concrete								
.5	2.5		Soil, dark brow								
2.5	4		Silty Clay (CL)								
4	4.5		Sand with fine								
4.5	20		Silty Clay (CL)								
20 25	25 TD		Clean Sands (S		OWII		-				
	10		LITE DOILLIO				+				
7 CONTO	ACTOR'S OF	LANDON	NER'S CERTIFICAT	ION: This wat	ar well was	(x) coasts:	cted (2) ross	netructed or /2	N plugged upd	for my juriedict	ion and w
Commisted	4010KS UK	LANDOW	INCR S CERTIFICAT	ion. This wate	er well was	(X) CONSTRU	vie record is t	rue to the best	n plugged und of my knowlad	ier my jurisuici	Kansas
Completed (on (mo/day/yr)	9/29/	505		And tr	lis record is t	nue to the best (or my knowled	daylus 101	20/2000
vvater Well	Contractor's L	license No	Associa	ted Enviro	nmantal	inis V	vater vveii Re	cora was comp	Rradiev 1	Johnson	LUI LUUJ
Under the b	UCTIONS: Pie	ease fill in h	lanks and circle the cor	rect answers. S	end three co	pies to Kans	as Departmen	nt of Health and E	nvironment. Bu	reau or waten	Togeka,
			913-296-5545. Send						0	100 11	