MW-50 GSI Job No. 117434 WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. Township Number Range Number 1 LOCATION OF WATER WELL: Fraction Section Number NW 1/4 27 13 18 R County: Distance and direction from nearest town or city street address of well if located within city? 3408 Vine St. - Hays 2 WATER WELL OWNER: Golden Ox RR#, St. Address, Box # : 3410 Vine St. Board of Agriculture, Division of Water Resources City, State, ZIP Code : **Hays, KS 67601**3 LOCATE WELL'S LOCATON WITH 4 DEPTH O Application Number: Depth(s) Groundwater Encountered 1 # 0 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL **22.65** ft. below TOC measured on mo/day/yr **02/14/12** -- NW --+-- NE --Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 14 in. to 30 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes ______No X ____ If yes, mo/day/yr sample was Water Well Disinfected? Yes No X submitted CASING JOINTS: Glued Clamped 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) Welded 6 Asbestos-Cement 9 Other (specify below) Threaded Flush 4 ABS 7 Fiberglass Blank casing diameter 5 in. to 15 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 7 PVC 10 Asbestos-cement TYPE OF SCREEN OR PERFORATION MATERIAL: 8 RMP (SR) 11 Other (specify) 1 Steel 3 Stainless steel 5 Fiberglass 6 Concrete tile 9 ABS 4 Galvanized steel 12 None used (open hole) 5 Gauzed wrapped 8 Saw cut SCREEN OR PERFORATION OPENINGS ARE: 11 None (open hole) 6 Wire wrapped 9 Drilled holes 3 Mill slot 1 Continuous slot 10 Other (specify) 7 Torch cut 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From 15 ft. to 30 ft. From ft. to ft.
 From
 ft. to
 ft. From
 ft. to
 ft.

 From
 13
 ft. to
 30
 ft. From
 ft. to
 ft.
 GRAVEL PACK INTERVALS: ft. From 3 Bentonite 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Grout Intervals From 1 ft. to 13 ft. From ft. to ft. From ft. to ft. 10 Livestock pens 14 Abandoned water well What is the nearest source of possible contamination: 11 Fuel storage 15 Oil well/ Gas well 1 Septic tank 4 Lateral lines 7 Pit privy 8 Sewage lagoon 12 Fertilizer storage 2 Sewer lines 5 Cess pool 16 Other (specify below) 13 Insecticide storage 3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? How many feet? CODE LITHOLOGIC LOG FROM PLUGGING INTERVALS TO FROM Topsoil 0 13 Clayey Silt, brown Sand, fine grained, light brown 13 16 16 Sandy Silt, brown 20 Clayey Silt, gray brown, with some 20 30 fine sand and gravel

Longitude: 99.31762 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 03/30/12 and this record is true to the best of my knowledge and belief. Kansas This Water Well Record was completed on (mo/day/yr) 04/05/12 Water Well Contractor's License No. by (signature) Geotechnical Services Inc.

Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W

Latitude: 38.89566