WATER WELL RECORD		Form WWC-5			ater Resources App. N	Io.	
1 LOCATION OF WA		Fraction		Section Number		Range Number	
County:		1/4 1/4 NW	14 NW 14	Clabal Basitian		R/8 DE KW	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here Latitude:							
nom nearest town or microscion. If it is what is a substitute of the substitute of t				Longitude: (in decimal degrees)			
		Elevation:					
2 WATER WELL OWNER: Cal Ziegler				Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 18 08 13 2516				GPS unit (Make/Model:)			
City, State, ZIP Code : Hays KS 67601				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL	. 1		•			] 3-13 m, ∐ ≥13 m	
WITH AN "X" IN		COMPLETED WEL					
SECTION BOX:							
N	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
1   1	EST. YIELD						
$W = \begin{bmatrix} -NW - 1 \\ \end{bmatrix} = \begin{bmatrix} E \end{bmatrix}$ Bore Hole Diameter $\mathcal{L}$ in. to $\mathcal{L}$ ft., and in. to ft.							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SWSE Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department?  Yes  No							
S If yes, mo/day/yr sample was submitted							
1 mile  Water well disinfected? ✓ Yes □ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot							
Louvered shutter    Key punched    Wire wrapped    Saw cut    Other (specify)							
SCREEN-PERFORATED INTERVALS:         From							
GRAVEL PACK INTERVALS: From 4.7							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From							
What is the nearest source of possible contamination:  Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
Watertight sewer lines  Seepage pit  Feedyard Fertilizer storage  Oil well/gas well  Direction from well  AST Distance from well  Solution							
FROM TO	LITHOLOG		FROM	TO LITHO	. LOG (cont.) or PLU	JGGING INTERVALS	
0 2 700							
2 36 CIA	Y DARK					•	
36 42 CIA		- LIGHT					
	JD + CIA	4					
45 48 3HA	ILE						
			,				
7 CONTRACTOR'S OF	LANDOWNEI	O'S CERTIFICATIO	N. This water	r well was 💆 co	estructed $\square$ reconst	nucted or Diplugged	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year).							
Kansas Water Well Contractor's License No. 44.0 This Water Well Record was completed on (mo/day/year)							
under the business name of Amale State Sta							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.							
http://www.kdneks.gov/waterweii/index.ntmi.  KSA 82a-1212							