				ER WELL RECORD Fo	rm WWC-5	KSA 82a-12	212 ID No			
LOCATION						n Number			ange Numbei	اسسسا
ounty:	El	lis	SE 1/4			28	т 13	S R	18	W
istance and d 2701 Vine \$			own or city street ac	ddress of well if located v	vithin city?					
			n Pfannenstie	1		·				
R#, St. Addre				•			Board of Agriculture	e. Division of	Water Resou	ırces
City, State, ZIF	Code	Hays	, KS 67601				Application Numbe			
LILOCATE W	'ELL'S LOC	ATON WIT	Ή!!	ne en la compaña de que la compaña de la comp ensa de la compaña de la compaña de la compaña de la compaña de la La compaña de la compaña d					-00	
AN "X" IN S	ECTION BO	OX:	MED TH OF I	COMPLETED WELL	52	ft. ELEV	'ATION:	2037,18 (1	UC)	:
1	! I			dwater Encountered 1						
1	<u>ښ</u>	NE		C WATER LEVEL						
w w				np test data: Well wate						
<u> </u>	!	!	Est. Yield	gpm: Well water	r was	π	. aπer	ours pumping		
		SE	WELL WATER	neter 6 in to TO BE USED AS: 5 P	ublic water sur	nnly	8 Air conditioning	11 Inject	tion well	11.
\	i		1 Domest	ic 3 Feed lot 6 C	il field water su	upply	9 Dewatering	12 Other	r (Specify be	low)
ا ا ا ا ا ا ا ا ا ا ا ا ا ا ا ا ا ا ا 		i x		n 4 Industrial 7 L						
	S			l/bacteriological sample :						
			submitted			Wa	ter Well Disinfected?	Yes	No X	
TYPE OF E	BLANK CAS	ING USED	Q:	5 Wrought Iron	8 Concret	te tile	CASING JOINTS:	Glued	Clamped	
1 Steel		3 RM	P (SR)	6 Asbestos-Cemen	t 9 Other (s	specify belo		Welded		
2 PVC		4 ABS	3	7 Fiberglass	والمرافر فالماك فرعات فالما	an a series and		Threaded	Flush	
3lank casing o	liameter	1	in. to 4	9 ft., Dia						ft.
Dasing height			0	in., weight	0.703	lbs./ft.	Wall thickness or gauge	ge No.	SCH. 40	
			ION MATERIAL:		17 1	2\/C	110 Ashestos	s-cement		
1 Steel			inless steel	5 Fiberglass	8 F	RMP (SR)	11 Other (sp	pecify)	وجاها مربعا فراجاتاني جاعون	
2 Brass			vanized steel	6 Concrete tile				ed (open hole).	
		-	NINGS ARE:				8 Saw cut	71. N	one (open no	ne)
	nuous slot		3 Mill slot		wrapped n cut		9 Drilled holes			
	ered shutter		4 Key punched			a 1	10 Other (specify)	4 40		
SCREEN-PEF	CORATED	IIVIERVAL	S. FIOIII	49 ft. to			Trom	ft to	. غوامر خارث پداندربها تحاط کا پ	ft.
CDAV	EL PACK I	NITEDVAL 6	From	ft. to 47 ft. to	52		From	ft to		ff.
GIVAV	ELFACK	INTELY VALV		ft. to						ft.
6 CPOUT M	ATEDIAL:	1 No		2 Cement grout		onite				
				ft. From					amanbakasa Ka	4
Grout interval	s FIUIII	o of noceih	le contamination:	IL FION	IL II	10 Lives	stock pens	14 Abandone	o ad water well	
				s 7 Pit priv	i		storage			
2 Sewe			5 Cess pool				Andrew Company	16 Other (sp		
3 Wate	rtight sewer	lines	6 Seepage pi		-	13 Insec	cticide storage			
Direction from	well?					How many	/ feet?			
FROM	TO	CODE		OLOGIC LOG	FROM	ТО	PLUG	SING INTERV	ALS	
0	0.5		Concrete			<u> </u>		langhalang di	<u></u>	<u></u>
0.5	52			wn, gray brown below between 15' and 25'	'					
- 0,0			TO , LI GOO GUITOTTO	, , , , , , , , , , , , , , , , , , , ,						
						ļ				
						-		<u> </u>	<u> </u>	
						+	<u> </u>		a	
	<u></u>	 				<u> </u>	Survey report of	date: 06/2	1/13	
	 			· · ·		+	Latitude: N 38.	885972	5	
	admired to			The state of the s			Longitude: W 9			
7 CONTRAC	CTOR'S OF	LANDOW	NER'S CERTIFICA	ATION: This water well w	as (1) construc	ted , (2) rec	onstructed, or (3) plugg	jed under my j	urisdiction an	d was
completed on	(mo/day/yr)	03,	/27/13	and th	is record is	true to the best of my	knowledge an	d belief. Kar	nsas
Water Well C	ontractor's	License No		531	This W	Vater Well F	Record was completed	on (mo/day/y	r) 06/24	V13
under the bus	sinėss name	e of	GSI En	igineering, LLC	by	(signature)	MA MA			
INSTRU	CTIONS: P	lease fill in b	lanks and circle the c	correct answers. Send three	e copies to Kans	as Departme	ent of Hèalth and Enviror	ment, Bureau o	of Water, 1000	SW